

# Statement of Basis of the Federal Operating Permit

CITGO Refining and Chemicals Company L.P.

Site Name: CITGO Corpus Christi Refinery East Plant  
Area Name: Corpus Christi Refinery East Plant and Terminal  
Physical Location: 1801 Nueces Bay Blvd  
Nearest City: Corpus Christi  
County: Nueces

Permit Number: O1423  
Project Type: Minor Revision

The North American Industry Classification System (NAICS) Code: 324110  
NAICS Name: Petroleum Refineries

This Statement of Basis sets forth the legal and factual basis for the draft changes to the permit conditions resulting from the minor revision project in accordance with 30 TAC §122.201(a)(4). The applicant has submitted an application for a minor permit revision per §§ 122.215-217. This document includes the following information:

- A description of the facility/area process description;
- A description of the revision project;
- A basis for applying permit shields;
- A list of the federal regulatory applicability determinations;
- A table listing the determination of applicable requirements;
- A list of the New Source Review Requirements;
- The rationale for periodic monitoring methods selected; and
- A list of available unit attribute forms.

Prepared on: February 14, 2019

## **Operating Permit Basis of Determination**

### **Description of Revisions**

The federal operating permit was revised to add New Source Review permit 149242 that was issued on December 12, 2018 to the New Source Review Authorization References Table. The NSR permit authorized molten sulfur loading into tank trucks and railcars at the Corpus Christi Refinery East Plant.

### **Permit Area Process Description**

The East Plant Refinery consists of several integrated petroleum and petrochemical processing units and key support facilities. Primary products produced include gasoline and petrochemical products. Some intermediate products are sent to the West Plant for further processing and returned for ultimate processing, while other East Plant intermediates are processed into diesel blending components and a coke sales product. Intermediate products are transported to and from the West Plant via interconnecting pipeline and barge docks.

The Crude and Vacuum Units are used to separate the crude oil by distillation into light naphtha, naphtha, kerosene, diesel, and gas oils in two steps. First, the total crude oil is fractionated in the atmospheric tower, then the high-boiling bottoms fraction is fed to the vacuum tower, operated at deep vacuum in order that fractionation takes place at the lowest possible vaporization temperature.

The No. 4 Unifiner's purpose is to catalytically remove compounds that poison or damage platformer reactor catalyst from naphtha feedstreams into the No. 4 Platformer Unit. A bimetallic catalyst is used to convert sulfur, nitrogen, oxygen, and organic metals into more easily removable compounds, and the saturation of some olefins into paraffins and isoparaffins is achieved.

The No. 4 Platformer is a catalytic reforming process employing a platinum catalyst to convert low-octane naphtha into high-octane full-range platformate product. Isomerization, hydrocracking, and dehydrocyclization take place here, and the platformate product is split to produce an aromatic-rich feedstock for the Udex unit and a high-octane blending component for gasoline.

The Unibon unit is designed to improve the quality of gas oils to make them suitable for upgrading in the Fluid Catalytic Cracking units. The principle contaminants, sulfur, nitrogen, and the metals nickel and vanadium, are replaced with hydrogen in the presence of catalyst. The treated gas oil is sent to fractionation to separate the lighter components from the treated stream prior to processing at the Cat Crackers.

The purpose of the No. 1 Fluid Catalytic Cracking Unit, consisting of an integrated catalyst section and fractionation section, is to convert heavy petroleum fractions like gas oils into more valuable fractions like raw gasoline.

The Hydrar Unit, designed to hydrogenate benzene into cyclohexane, consists of four sections - hydrogen cleaning, reactor, reactor product separator, and fractionation - that work together to remove impurities from the hydrogen stream, convert benzene into cyclohexane, and further refine the cyclohexane before sending it to storage.

The Cumene Process alkylates benzene, producing essentially pure isopropyl benzene, used primarily for the production of phenol and acetone. The BTX Unit extracts the valuable aromatics from the aromatic-rich platformate. The purpose of the Aromatics Disproportionation (ADP) Unit is to convert toluene into more desirable products such as xylene and benzene. The purpose of the MTBE Unit is to generate a methyl-tertiary-butyl-ether (MTBE) product through the condensation of isobutylene from refinery olefin streams with methanol. The ether product allows the blending of gasoline meeting the oxygenate requirements set forth in the 1990 Clean Air Act Amendments. The Molecular Sieve Dehydrator Unit is utilized to reduce the water content of Alkylate feed stream to less than 10 mole ppm.

The purpose of the C4 Selective Hydrogenation Process (C4SHP) is to improve the quality of the mixed C4 olefin stream that is used as Alkylation Unit feedstock. This is primarily achieved by removing the tar forming diolefins by catalytic saturation with hydrogen to form mono-olefins and saturates. Additional quality improvement is realized through the isomerization of 1-butylene to 2-butylene, resulting in increased alkylate octane. The C4SHP effluent is stripped to remove the light ends that accompany the make-up hydrogen and oxygenate contaminants from the upstream MTBE production unit before entering the Mole Sieve Unit for further treatment.

In the HF Alkylation Unit, olefins from the FCC, the West Plant Coker, and the MTBE units are combined with recycle isobutane to form alkylate. A secondary function of the unit is the separation and production of normal butane and propane.

The primary purpose of the Merox units is to convert "sour" smelling sulfur compounds (mercaptans) found in some gaseous and liquid petroleum sources to odorless "sweet" sulfur compounds. This is done by reacting two mercaptan compounds together in a solution of sodium hydroxide with catalyst to form a disulfide compound. In the sweetening version of the process, the charge stock is mixed with air and a solution of Merox catalyst, and the soluble disulfides keep the sulfur content of the charge constant. Another version of the Merox process, the extractive version, actually removes most of the sulfur while converting it to disulfides. The facility includes two sweetening units and three of the extractive variety.

The C3/C4 Splitter unit utilizes two distillation columns to separate a mixture of propylene and butylene, and the Fuel Gas Treating (Amine) Unit is used to remove sulfur-containing compounds from off-gases.

The No. 2 Fluid Catalytic Cracking Unit (FCCU) catalytically cracks the relatively heavy feed into lighter components, which are subsequently processed in the Gas Concentration unit or other refinery units. The bulk of the unit's products are blended into gasoline and heating oils or charged to other units for further processing.

The Gas Concentration unit consists of a primary absorber, sponge absorber, stripper, debutanizer, and depentanizer to separate the main column overhead product into LPG and gasoline streams.

The Saturates Gas Plant is a five-tower system of absorption followed by fractionation, designed to maximize the recovery of propane and heavier hydrocarbons from fuel gas while making separations in the following order: debutanizer, depropanizer, and depentanizer.

The Sulfur Recovery Unit converts sulfur-containing gases to elemental sulfur in an integrated process employing four units. The Sour Water Stripper is used to strip sulfur and ammonia-containing compounds from "sour water" produced by various hydrocarbon processing units. The Fuel Gas Treating (Amine) Unit is used to remove sulfur-containing compounds from off-gases produced by various hydrocarbon processing units. The Claus Sulfur Recovery unit converts H<sub>2</sub>S into elemental sulfur by means of thermal and catalytic reactions. The SCOT Tail Gas Treating unit is used to reconvert Claus reaction tail gas into H<sub>2</sub>S for the reintroduction to the Claus sulfur recovery process.

Refinery process wastewater is treated in three basic stages. In Primary Wastewater Treatment, oil and other suspended contaminants are gravity-separated from the process water in the Oil/water Corrugated Plate Interceptor Separator. Recovered oil is re-processed in the refinery, and the clarified water is sent to the intermediate treatment phase.

Intermediate Treatment takes place in the Dissolved Air Flootation Unit, where the recycle stream is super-saturated with dissolved air, then released to the floatation unit at atmospheric pressure, and surrounded by minute bubbles that carry the suspended particles to the surface, where they're removed by a skimming mechanism.

In Secondary Treatment, organic waste is further treated by biological activity in the aerated basins. Microorganisms convert the organic waste to end products such as carbon dioxide, water, and methane, and the clarified water is released into the Corpus Christi Inner Harbor waterway.

## **FOPs at Site**

The "application area" consists of the emission units and that portion of the site included in the application and this permit. Multiple FOPs may be issued to a site in accordance with 30 TAC § 122.201(e). When there is only one area for the site, then the application information and permit will include all units at the site. Additional FOPs that exist at the site, if any, are listed below.

Additional FOPs: O3542

## Major Source Pollutants

The table below specifies the pollutants for which the site is a major source:

Major Pollutants	VOC, SO <sub>2</sub> , PM, NO <sub>x</sub> , HAPs, CO
------------------	---

## Reading State of Texas's Federal Operating Permit

The Title V Federal Operating Permit (FOP) lists all state and federal air emission regulations and New Source Review (NSR) authorizations (collectively known as “applicable requirements”) that apply at a particular site or permit area (in the event a site has multiple FOPs). **The FOP does not authorize new emissions or new construction activities.** The FOP begins with an introductory page which is common to all Title V permits. This page gives the details of the company, states the authority of the issuing agency, requires the company to operate in accordance with this permit and 30 Texas Administrative Code (TAC) Chapter 122, requires adherence with NSR requirements of 30 TAC Chapter 116, and finally indicates the permit number and the issuance date.

This is followed by the table of contents, which is generally composed of the following elements. Not all permits will have all of the elements.

- General Terms and Conditions
- Special Terms and Conditions
  - Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting
  - Additional Monitoring Requirements
  - New Source Review Authorization Requirements
  - Compliance Requirements
  - Protection of Stratosphere Ozone
  - Permit Location
  - Permit Shield (30 TAC § 122.148)
- Attachments
  - Applicable Requirements Summary
    - Unit Summary
    - Applicable Requirements Summary
  - Additional Monitoring Requirements
  - Permit Shield
  - New Source Review Authorization References
  - Compliance Plan
  - Alternative Requirements
- Appendix A
  - Acronym list
- Appendix B
  - Copies of major NSR authorizations

### General Terms and Conditions

The General Terms and Conditions are the same and appear in all permits. The first paragraph lists the specific citations for 30 TAC Chapter 122 requirements that apply to all Title V permit holders. The second paragraph describes the requirements for record retention. The third paragraph provides details for voiding the permit, if applicable. The fourth paragraph states that the permit holder shall comply with the requirements of 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit. The fifth paragraph provides details on submission of reports required by the permit.

### Special Terms and Conditions

Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting. The TCEQ has designated certain applicable requirements as site-wide requirements. A site-wide requirement is a requirement that

applies uniformly to all the units or activities at the site. Units with only site-wide requirements are addressed on Form OP-REQ1 and are not required to be listed separately on an OP-UA Form or Form OP-SUM. Form OP-SUM must list all units addressed in the application and provide identifying information, applicable OP-UA Forms, and preconstruction authorizations. The various OP-UA Forms provide the characteristics of each unit from which applicable requirements are established. Some exceptions exist as a few units may have both site-wide requirements and unit specific requirements.

Other conditions. The other entries under special terms and conditions are in general terms referring to compliance with the more detailed data listed in the attachments.

## Attachments

Applicable Requirements Summary. The first attachment, the Applicable Requirements Summary, has two tables, addressing unit specific requirements. The first table, the Unit Summary, includes a list of units with applicable requirements, the unit type, the applicable regulation, and the requirement driver. The intent of the requirement driver is to inform the reader that a given unit may have several different operating scenarios and the differences between those operating scenarios.

The applicable requirements summary table provides the detailed citations of the rules that apply to the various units. For each unit and operating scenario, there is an added modifier called the "index number," detailed citations specifying monitoring and testing requirements, recordkeeping requirements, and reporting requirements. The data for this table are based on data supplied by the applicant on the OP-SUM and various OP-UA forms.

Additional Monitoring Requirement. The next attachment includes additional monitoring the applicant must perform to ensure compliance with the applicable standard. Compliance assurance monitoring (CAM) is often required to provide a reasonable assurance of compliance with applicable emission limitations/standards for large emission units that use control devices to achieve compliance with applicant requirements. When necessary, periodic monitoring (PM) requirements are specified for certain parameters (i.e. feed rates, flow rates, temperature, fuel type and consumption, etc.) to determine if a term and condition or emission unit is operating within specified limits to control emissions. These additional monitoring approaches may be required for two reasons. First, the applicable rules do not adequately specify monitoring requirements (exception- Maximum Achievable Control Technology Standards (MACTs) generally have sufficient monitoring), and second, monitoring may be required to fill gaps in the monitoring requirements of certain applicable requirements. In situations where the NSR permit is the applicable requirement requiring extra monitoring for a specific emission unit, the preferred solution is to have the monitoring requirements in the NSR permit updated so that all NSR requirements are consolidated in the NSR permit.

Permit Shield. A permit may or may not have a permit shield, depending on whether an applicant has applied for, and justified the granting of, a permit shield. A permit shield is a special condition included in the permit document stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirement(s) or specified applicable state-only requirement(s).

New Source Review Authorization References. All activities which are related to emissions in the state of Texas must have a NSR authorization prior to beginning construction. This section lists all units in the permit and the NSR authorization that allowed the unit to be constructed or modified. Units that do not have unit specific applicable requirements other than the NSR authorization do not need to be listed in this attachment. While NSR permits are not physically a part of the Title V permit, they are legally incorporated into the Title V permit by reference. Those NSR permits whose emissions exceed certain PSD/NA thresholds must also undergo a Federal review of federally regulated pollutants in addition to review for state regulated pollutants.

Compliance Plan. A permit may have a compliance schedule attachment for listing corrective actions plans for any emission unit that is out of compliance with an applicable requirement.

Alternative Requirements. This attachment will list any alternative monitoring plans or alternative means of compliance for applicable requirements that have been approved by the EPA Administrator and/or the TCEQ Executive Director.

## Appendix A

Acronym list. This attachment lists the common acronyms used when discussing the FOPs.

## Appendix B

Copies of major NSR authorizations applicable to the units covered by this permit have been included in this Appendix, to ensure that all interested persons can access those authorizations.

### **Stationary vents subject to 30 TAC Chapter 111, Subchapter A, § 111.111(a)(1)(B) addressed in the Special Terms and Conditions**

The site contains stationary vents with a flowrate less than 100,000 actual cubic feet per minute (acfm) and constructed after January 31, 1972 which are limited, over a six-minute average, to 20% opacity as required by 30 TAC § 111.111(a)(1)(B). As a site may have a large number of stationary vents that fall into this category, they are not required to be listed individually in the permit's Applicable Requirement Summary. This is consistent with EPA's White Paper for Streamlined Development of Part 70 Permit Applications, July 10, 1995, that states that requirements that apply identically to emission units at a site can be treated on a generic basis such as source-wide opacity limits.

Periodic monitoring is specified in Special Term and Condition 3 for stationary vents subject to 30 TAC § 111.111(a)(1)(B) to verify compliance with the 20% opacity limit. These vents are not expected to produce visible emissions during normal operation. The TCEQ evaluated the probability of these sources violating the opacity standards and determined that there is a very low potential that an opacity standard would be exceeded. It was determined that continuous monitoring for these sources is not warranted as there would be very limited environmental benefit in continuously monitoring sources that have a low potential to produce visible emissions. Therefore, the TCEQ set the visible observation monitoring frequency for these sources to once per calendar quarter.

The TCEQ has exempted vents that are not capable of producing visible emissions from periodic monitoring requirements. These vents include sources of colorless VOCs, non-fuming liquids, and other materials that cannot produce emissions that obstruct the transmission of light. Passive ventilation vents, such as plumbing vents, are also included in this category. Since this category of vents are not capable of producing opacity due to the physical or chemical characteristics of the emission source, periodic monitoring is not required as it would not yield any additional data to assure compliance with the 20% opacity standard of 30 TAC § 111.111(a)(1)(B).

In the event that visible emissions are detected, either through the quarterly observation or other credible evidence, such as observations from company personnel, the permit holder shall either report a deviation or perform a Test Method 9 observation to determine the opacity consistent with the 6-minute averaging time specified in 30 TAC § 111.111(a)(1)(B). An additional provision is included to monitor combustion sources more frequently than quarterly if alternate fuels are burned for periods greater than 24 consecutive hours. This will address possible emissions that may arise when switching fuel types.

### **Stationary Vents subject to 30 TAC Chapter 111 not addressed in the Special Terms and Conditions**

All other stationary vents subject to 30 TAC Chapter 111 not covered in the Special Terms and Conditions are listed in the permit's Applicable Requirement Summary. The basis for the applicability determinations for these vents are listed in the Determination of Applicable Requirements table.

## Federal Regulatory Applicability Determinations

The following chart summarizes the applicability of the principal air pollution regulatory programs to the permit area:

Regulatory Program	Applicability (Yes/No)
Prevention of Significant Deterioration (PSD)	Yes
Nonattainment New Source Review (NNSR)	No
Minor NSR	Yes
40 CFR Part 60 - New Source Performance Standards	Yes
40 CFR Part 61 - National Emission Standards for Hazardous Air Pollutants (NESHAPs)	Yes
40 CFR Part 63 - NESHAPs for Source Categories	Yes
Title IV (Acid Rain) of the Clean Air Act (CAA)	No
Title V (Federal Operating Permits) of the CAA	Yes
Title VI (Stratospheric Ozone Protection) of the CAA	Yes
CSAPR (Cross-State Air Pollution Rule)	No
Federal Implementation Plan for Regional Haze (Texas SO <sub>2</sub> Trading Program)	No

## Basis for Applying Permit Shields

An operating permit applicant has the opportunity to specifically request a permit shield to document that specific applicable requirements do not apply to emission units in the permit. A permit shield is a special condition stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements. A permit shield has been requested in the application for specific emission units. For the permit shield requests that have been approved, the basis of determination for regulations that the owner/operator need not comply with are located in the "Permit Shield" attachment of the permit.

## Insignificant Activities

In general, units not meeting the criteria for inclusion on either Form OP-SUM or Form OP-REQ1 are not required to be addressed in the operating permit application. Examples of these types of units include, but are not limited to, the following:

1. Office activities such as photocopying, blueprint copying, and photographic processes.
2. Sanitary sewage collection and treatment facilities other than those used to incinerate wastewater treatment plant sludge. Stacks or vents for sanitary sewer plumbing traps are also included.
3. Food preparation facilities including, but not limited to, restaurants and cafeterias used for preparing food or beverages primarily for consumption on the premises.
4. Outdoor barbecue pits, campfires, and fireplaces.

5. Laundry dryers, extractors, and tumblers processing bedding, clothing, or other fabric items generated primarily at the premises. This does not include emissions from dry cleaning systems using perchloroethylene or petroleum solvents.
6. Facilities storing only dry, sweet natural gas, including natural gas pressure regulator vents.
7. Any air separation or other industrial gas production, storage, or packaging facility. Industrial gases, for purposes of this list, include only oxygen, nitrogen, helium, neon, argon, krypton, and xenon.
8. Storage and handling of sealed portable containers, cylinders, or sealed drums.
9. Vehicle exhaust from maintenance or repair shops.
10. Storage and use of non-VOC products or equipment for maintaining motor vehicles operated at the site (including but not limited to, antifreeze and fuel additives).
11. Air contaminant detectors and recorders, combustion controllers and shut-off devices, product analyzers, laboratory analyzers, continuous emissions monitors, other analyzers and monitors, and emissions associated with sampling activities. Exception to this category includes sampling activities that are deemed fugitive emissions and under a regulatory leak detection and repair program.
12. Bench scale laboratory equipment and laboratory equipment used exclusively for chemical and physical analysis, including but not limited to, assorted vacuum producing devices and laboratory fume hoods.
13. Steam vents, steam leaks, and steam safety relief valves, provided the steam (or boiler feedwater) has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
14. Storage of water that has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
15. Well cellars.
16. Fire or emergency response equipment and training, including but not limited to, use of fire control equipment including equipment testing and training, and open burning of materials or fuels associated with firefighting training.
17. Crucible or pot furnaces with a brim full capacity of less than 450 cubic inches of any molten metal.
18. Equipment used exclusively for the melting or application of wax.
19. All closed tumblers used for the cleaning or deburring of metal products without abrasive blasting, and all open tumblers with a batch capacity of 1,000 lbs. or less.
20. Shell core and shell mold manufacturing machines.
21. Sand or investment molds with a capacity of 100 lbs. or less used for the casting of metals;
22. Equipment used for inspection of metal products.
23. Equipment used exclusively for rolling, forging, pressing, drawing, spinning, or extruding either hot or cold metals by some mechanical means.
24. Instrument systems utilizing air, natural gas, nitrogen, oxygen, carbon dioxide, helium, neon, argon, krypton, and xenon.
25. Battery recharging areas.
26. Brazing, soldering, or welding equipment.

### **Determination of Applicable Requirements**

The tables below include the applicability determinations for the emission units, the index number(s) where applicable, and all relevant unit attribute information used to form the basis of the applicability determination. The unit attribute information is a description of the physical properties of an emission unit which is used to determine the requirements to which the permit holder must comply. For more information about the descriptions of the unit attributes specific Unit Attribute Forms may be viewed at [www.tceq.texas.gov/permitting/air/nav/air\\_all\\_ua\\_forms.html](http://www.tceq.texas.gov/permitting/air/nav/air_all_ua_forms.html).

A list of unit attribute forms is included at the end of this document. Some examples of unit attributes include construction date; product stored in a tank; boiler fuel type; etc.. Generally, multiple attributes are needed to determine the requirements for a given emission unit and index number. The table below lists these attributes in the column entitled "Basis of Determination." Attributes that demonstrate that an applicable requirement applies will be the factual basis for the specific citations in an applicable requirement that apply to a unit for that index number. The TCEQ Air Permits Division has developed flowcharts for determining applicability of state and federal regulations based on the unit attribute information in a Decision Support System (DSS). These flowcharts can be accessed via the internet at [www.tceq.texas.gov/permitting/air/nav/air\\_supportsys.html](http://www.tceq.texas.gov/permitting/air/nav/air_supportsys.html). The Air Permits Division staff may also be contacted for assistance at (512) 239-1250.



The attributes for each unit and corresponding index number provide the basis for determining the specific legal citations in an applicable requirement that apply, including emission limitations or standards, monitoring, recordkeeping, and reporting. The rules were found to apply or not apply by using the unit attributes as answers to decision questions found in the flowcharts of the DSS. Some additional attributes indicate which legal citations of a rule apply. The legal citations that apply to each emission unit may be found in the Applicable Requirements Summary table of the draft permit. There may be some entries or rows of units and rules not found in the permit, or if the permit contains a permit shield, repeated in the permit shield area. These are sets of attributes that describe negative applicability, or; in other words, the reason why a potentially applicable requirement does not apply.

If applicability determinations have been made which differ from the available flowcharts, an explanation of the decisions involved in the applicability determination is specified in the column "Changes and Exceptions to RRT." If there were no exceptions to the DSS, then this column has been removed.

The draft permit includes all emission limitations or standards, monitoring, recordkeeping and reporting required by each applicable requirement. If an applicable requirement does not require monitoring, recordkeeping, or reporting, the word "None" will appear in the Applicable Requirements Summary table. If additional periodic monitoring is required for an applicable requirement, it will be explained in detail in the portion of this document entitled "Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected."

When attributes demonstrate that a unit is not subject to an applicable requirement, the applicant may request a permit shield for those items. The portion of this document entitled "Basis for Applying Permit Shields" specifies which units, if any, have a permit shield.

#### Operational Flexibility

When an emission unit has multiple operating scenarios, it will have a different index number associated with each operating condition. This means that units are permitted to operate under multiple operating conditions. The applicable requirements for each operating condition are determined by a unique set of unit attributes. For example, a tank may store two different products at different points in time. The tank may, therefore, need to comply with two distinct sets of requirements, depending on the product that is stored. Both sets of requirements are included in the permit, so that the permit holder may store either product in the tank.

### Determination of Applicable Requirements

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
065-P-35	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = The site is a major source of hazardous air pollutants as defined in 40 CFR § 63.2</p> <p>Brake HP = Stationary RICE with a brake HP greater than 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p>	None
065-P-36	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = The site is a major source of hazardous air pollutants as defined in 40 CFR § 63.2</p> <p>Brake HP = Stationary RICE with a brake HP greater than 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p>	None
065-P-37	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = The site is a major source of hazardous air pollutants as defined in 40 CFR § 63.2</p> <p>Brake HP = Stationary RICE with a brake HP greater than 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p>	None
065-P-38	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = The site is a major source of hazardous air pollutants as defined in 40 CFR § 63.2</p> <p>Brake HP = Stationary RICE with a brake HP greater than 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p>	None
11-H1	40 CFR Part 63, Subpart DDDDD	63DDDDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
11-H2	40 CFR Part 63, Subpart DDDDD	63DDDDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
14-H1	40 CFR Part 63, Subpart DDDDD	63DDDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
14-H1	40 CFR Part 60, Subpart Dc	60DC-BOIL3	Construction/Modification Date = On or before June 9, 1989.	None
14-H1	40 CFR Part 60, Subpart J	60J-FUEL01	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).  Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.  Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO <sub>2</sub> emissions into the atmosphere.	None
17-H1	40 CFR Part 63, Subpart DDDDD	63DDDDD-02	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
17-INC	40 CFR Part 60, Subpart J	60J-FUEL01	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).  Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.  Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO <sub>2</sub> emissions into the atmosphere.	None
17-V30	40 CFR Part 60, Subpart NNN	60NNN-02	Subpart NNN Chemicals = The distillation unit does not produce any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.	None
18-E22	40 CFR Part 60, Subpart NNN	60NNN-02	Subpart NNN Chemicals = The distillation unit does not produce any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.	None
18-E22	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	R5115D-01	Alternate Control Requirement = The TCEQ Executive Director has not approved an alternate control requirement for demonstrating and documenting compliance or no such alternate has been requested.  Weight of VOC Emitted = Combined weight of VOC is 100 pounds (45.4 kg) or less in any consecutive 24-hour period.	None
18-HOTWELL	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	R5115D-01	Alternate Control Requirement = The TCEQ Executive Director has not approved an alternate control requirement for demonstrating and documenting compliance or no such alternate has been requested.  Weight of VOC Emitted = Combined weight of VOC is 100 pounds (45.4 kg) or less in any consecutive 24-hour period.	None
19-H1	40 CFR Part 63, Subpart DDDDD	63DDDDD-02	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
19-H1	40 CFR Part 60, Subpart J	60J-FUEL01	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007. Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO <sub>2</sub> emissions into the atmosphere.	None
19-H2	40 CFR Part 63, Subpart DDDDD	63DDDDD-02	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
19-H2	40 CFR Part 60, Subpart J	60J-FUEL01	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007. Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO <sub>2</sub> emissions into the atmosphere.	None
19-V28	40 CFR Part 60, Subpart NNN	60NNN-03	Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate. Construction/Modification Date = On or before December 30, 1983.	None
204-U942	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
204-U942	40 CFR Part 60, Subpart GGG	60GGG-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS IN VOC SERVICE SUBJECT TO NSPS GGG WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
207-H-1	40 CFR Part 63, Subpart DDDDD	63DDDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
21-H1A	40 CFR Part 63, Subpart DDDDD	63DDDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
21-H1B	40 CFR Part 63, Subpart DDDDD	63DDDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
23-TK0002A	30 TAC Chapter 115, Storage of VOCs	R5112	Tank Description = Tank does not require emission controls Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
23-TK0002A	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
28-H1	40 CFR Part 63, Subpart DDDDD	63DDDDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
28-H3	40 CFR Part 63, Subpart DDDDD	63DDDDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
29-H1 C&D	40 CFR Part 63, Subpart DDDDD	63DDDDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
29-H1A	40 CFR Part 63, Subpart DDDDD	63DDDDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
29-H1A	40 CFR Part 60, Subpart J	60J-FUEL01	<p>Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO<sub>2</sub> emissions into the atmosphere.</p>	None
29-H1B	40 CFR Part 63, Subpart DDDDD	63DDDDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
29-H2B	40 CFR Part 63, Subpart DDDDD	63DDDDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
29-H2B	40 CFR Part 60, Subpart J	60J-FUEL01	<p>Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO<sub>2</sub> emissions into the atmosphere.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
29-H3	40 CFR Part 63, Subpart DDDDD	63DDDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
29-TK0105	40 CFR Part 63, Subpart EEEE	63EEEE	Product Stored = Organic HAP containing liquid other than crude oil.	None
29-V26	40 CFR Part 63, Subpart UUU	63UUU-CRU	<p>CRU HCl Emission Limitation = Existing cyclic or continuous CRU reducing uncontrolled emissions of HCl by 97% by weight or to a concentration of 10 ppmv.</p> <p>CRU TOC Emission Limitation = Reduce uncontrolled emissions of TOC or nonmethane TOC by 98% by weight or to a concentration of 20 ppmv (Option 2).</p> <p>CRU HCl Control Device = Moving-bed gas-solid adsorption system.</p> <p>CRU TOC Control Device = Process Heater with a design heat input capacity &lt; 44 MW or in which all vent streams not introduced into the flame zone.</p> <p>CRU Bypass Line = Use a manual lock system by installing a car-seal or lock-and-key device.</p>	None
31-FCCU2	40 CFR Part 63, Subpart UUU	63UUU-1	<p>CCU CO Emission Limitation = CCU subject to the NSPS for CO in 40 CFR § 60.103 or electing to comply with the NSPS requirements (Option 1).</p> <p>CCU PM/Opacity Emission Limitation = CCU subject to the NSPS for PM in 40 CFR §60.102 - PM emissions not to exceed 1.0 kg/1,000 kg of coke burn-off in the catalyst regenerator and opacity of emissions not to exceed 30%, except for one 6-minute avg. opacity reading in any 1-hour period.</p> <p>CCU PM Control Device = Electrostatic Precipitator serving CCU over 20,000 barrels/day fresh feed capacity.</p> <p>CCU CO Monitoring Method = Continuous Emissions Monitoring System for measuring CO concentration.</p> <p>CCU PM Monitoring Method = Continuous Opacity Monitoring System.</p> <p>CCU Bypass Line = No bypass line serving the catalytic cracking unit.</p> <p>Alternate Method for Measuring Gas Flow Rate = Not using an alternate method for measuring gas flow rate as listed in §63.1573(a)(1).</p>	None
31-PR-1	30 TAC Chapter 111, Visible Emissions	111-VENT02	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = A continuous emissions monitoring system (CEMS) capable of measuring the opacity of emissions is installed in the vent in accordance with 30 TAC § 111.111(a)(1)(C).</p> <p>Total Feed Capacity = Total feed capacity is greater than 20,000 barrels per day.</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
38-FCCU1	40 CFR Part 63, Subpart UUU	63UUU-2	<p>CCU CO Emission Limitation = CCU subject to the NSPS for CO in 40 CFR § 60.103 or electing to comply with the NSPS requirements (Option 1).</p> <p>CCU PM/Opacity Emission Limitation = CCU subject to the NSPS for PM in 40 CFR §60.102 - PM emissions not to exceed 1.0 kg/1,000 kg of coke burn-off in the catalyst regenerator and opacity of emissions not to exceed 30%, except for one 6-minute avg. opacity reading in any 1-hour period.</p> <p>CCU PM Control Device = No PM control device.</p> <p>CCU CO Monitoring Method = Continuous Emissions Monitoring System for measuring CO concentration.</p> <p>CCU PM Monitoring Method = Continuous Opacity Monitoring System.</p> <p>CCU Bypass Line = No bypass line serving the catalytic cracking unit.</p> <p>Alternate Method for Measuring Gas Flow Rate = Not using an alternate method for measuring gas flow rate as listed in §63.1573(a)(1).</p>	None
38-H2	40 CFR Part 60, Subpart J	60J-FUEL03	<p>Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = On or before June 11, 1973.</p>	None
41-H1	40 CFR Part 63, Subpart DDDDD	63DDDDD-02	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
41-H2	40 CFR Part 63, Subpart DDDDD	63DDDDD-02	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
41-U41	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
41-U41	40 CFR Part 60, Subpart GGGa	60GGGa-1	<p>Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006.</p> <p>Equipment Components = Components are present.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
41-U41	40 CFR Part 63, Subpart CC	63CCVV-1	<p>CLOSED VENT (OR VAPOR COLLECTION) SYSTEMS = YES</p> <p>ENCLOSED COMBUSTION DEVICE = NO</p> <p>EXISTING SOURCE = YES</p> <p>FLARE = YES</p> <p>VAPOR RECOVERY SYSTEM = YES</p> <p>CLOSED VENT (OR VAPOR COLLETION) SYSTEMS EQUIVALENT EMISSION LIMITATION = NO</p> <p>COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES</p> <p>FLARE EQUIVALENT EMISSION LIMITATION = NO</p> <p>VAPOR RECOVERY SYSTEM EQUIVALENT EMISSION LIMITATION = NO</p> <p>AMEL = NO</p> <p>CLOSED VENT (OR VAPOR COLLETION) SYSTEMS COMPLYING WITH § 60.482-10 = YES</p> <p>FLARE COMPLYING WITH §60.482-10 = YES</p> <p>VAPOR RECOVERY SYSTEM COMPLYING WITH § 60.482-10 = YES</p>	None
41-U41	40 CFR Part 63, Subpart CC	63CCVV-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC/VHAP FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO MACT CC AND COMPLYING WITH NSPS VV REQUIREMENTS WITH NO ALTERNATE CONTROL OR CONTROL DEVICES	None
44-V10	30 TAC Chapter 115, Vent Gas Controls	R5VT-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is less than 30,000 ppmv.</p>	None
47-TK0103	30 TAC Chapter 115, Storage of VOCs	115-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	None



Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
47-U47	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
47-U47	40 CFR Part 60, Subpart GGG	60GGG-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS IN VOC SERVICE SUBJECT TO NSPS GGG WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
51-F413A	30 TAC Chapter 111, Visible Emissions	111-F1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used only under emergency or upset conditions.	None
51-F413A	40 CFR Part 60, Subpart A	60A-1	Subject to 40 CFR § 60.18 = Flare is not subject to 40 CFR § 60.18.	None
51-F413A	40 CFR Part 63, Subpart A	63A-1	Required Under 40 CFR Part 63 = Flare is not required by a Subpart under 40 CFR Part 63.	None
51-TK0001	40 CFR Part 63, Subpart CC	63CC-TK01	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.	None
52-U52AMNE	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
52-U52AMNE	40 CFR Part 63, Subpart CC	63CCVV-1	<p>CLOSED VENT (OR VAPOR COLLECTION) SYSTEMS = YES</p> <p>ENCLOSED COMBUSTION DEVICE = NO</p> <p>EXISTING SOURCE = YES</p> <p>FLARE = YES</p> <p>VAPOR RECOVERY SYSTEM = YES</p> <p>CLOSED VENT (OR VAPOR COLLETION) SYSTEMS EQUIVALENT EMISSION LIMITATION = NO</p> <p>COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES</p> <p>FLARE EQUIVALENT EMISSION LIMITATION = NO</p> <p>VAPOR RECOVERY SYSTEM EQUIVALENT EMISSION LIMITATION = NO</p> <p>AMEL = NO</p> <p>CLOSED VENT (OR VAPOR COLLETION) SYSTEMS COMPLYING WITH § 60.482-10 = YES</p> <p>FLARE COMPLYING WITH §60.482-10 = YES</p> <p>VAPOR RECOVERY SYSTEM COMPLYING WITH § 60.482-10 = YES</p>	None
52-U52AMNE	40 CFR Part 63, Subpart CC	63CCVV-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC/VHAP FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO MACT CC AND COMPLYING WITH NSPS VV REQUIREMENTS WITH NO ALTERNATE CONTROL OR CONTROL DEVICES	None
52-U52SRU	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
53-U53	40 CFR Part 60, Subpart J	60J-FUEL01	<p>Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO<sub>2</sub> emissions into the atmosphere.</p>	None
54-F414A	30 TAC Chapter 111, Visible Emissions	111-F1	<p>Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1.</p> <p>Emergency/Upset Conditions Only = Flare is used only under emergency or upset conditions.</p>	None
54-F414A	40 CFR Part 60, Subpart A	60A-1	Subject to 40 CFR § 60.18 = Flare is not subject to 40 CFR § 60.18.	None
54-F414A	40 CFR Part 63, Subpart A	63A-1	Required Under 40 CFR Part 63 = Flare is not required by a Subpart under 40 CFR Part 63.	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
54-TK3	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
54-TK3	40 CFR Part 60, Subpart Kb	60KB-TK11	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	None
56-U56	40 CFR Part 60, Subpart J	60J-FUEL01	<p>Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO<sub>2</sub> emissions into the atmosphere.</p>	None
57-D7	30 TAC Chapter 115, Loading and Unloading of VOC	115-LOAD22	Chapter 115 Facility Type = Marine terminal	None
57-D7	40 CFR Part 61, Subpart BB	61BB-LOAD2	Negative Applicability = The loading rack loads only benzene-laden waste, gasoline, crude oil, natural gas liquids, petroleum distillates or benzene-laden liquid from a coke by-product plant.	None
57-D7	40 CFR Part 63, Subpart CC	63Y-LOAD01	<p>Specified in 63.640(g)(1)-(6) = The gasoline loading rack or marine vessel loading operation is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The gasoline loading rack or marine vessel loading operation is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Unit Type = Marine vessel loading operation at a petroleum refinery meeting the applicability criteria of 40 CFR § 63.560.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
57-D7	40 CFR Part 63, Subpart Y	63Y-LOAD01	<p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Ballasting operations are the only operations performed at the facility.</p> <p>Vapor Pressure = Vapor pressure is less than 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p> <p>Subpart BB Applicability = Marine vessel loading operations are not subject to and complying with 40 CFR Part 61, Subpart BB.</p> <p>Material Loaded = Gasoline.</p> <p>HAP Impurities Only = Marine vessel loading operations at loading berths transfer liquids containing organic hazardous air pollutants other than as impurities.</p> <p>Source Emissions = Source with emissions of 10 or 25 tons.</p> <p>Throughput = Source with throughput of 10 M barrels or 200 M barrels.</p>	None
57-D7	40 CFR Part 63, Subpart Y	63Y-LOAD02	<p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Pressure = Vapor pressure is less than 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
57-D7	40 CFR Part 63, Subpart Y	63Y-LOAD03	<p>CEMS = Continuous emissions monitoring system (CEMS) is not being used.</p> <p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Balancing System = Emissions are not reduced by a vapor balancing system.</p> <p>Documenting Vapor Tightness = Electing to comply with the vapor tightness documentation in 40 CFR 63.567(b)(5)(ii).</p> <p>Vapor Pressure = Vapor pressure is greater than or equal to 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p> <p>Subpart BB Applicability = Marine vessel loading operations are not subject to and complying with 40 CFR Part 61, Subpart BB.</p> <p>Subpart Y Control Device Type = Combustion device other than flare or boiler.</p> <p>Material Loaded = Gasoline.</p> <p>HAP Impurities Only = Marine vessel loading operations at loading berths transfer liquids containing organic hazardous air pollutants other than as impurities.</p> <p>Performance Test = Baseline temperature from performance test.</p> <p>Alternate Monitoring = Complying with the control device specific monitoring procedures in 40 CFR § 63.564.</p> <p>Source Emissions = Source with emissions of 10 or 25 tons.</p> <p>Alternate Test Procedure = Electing to comply with the alternate test procedures in 40 CFR § 63.565(m).</p> <p>Throughput = Source with throughput of 10 M barrels or 200 M barrels.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
57-D7	40 CFR Part 63, Subpart Y	63Y-LOAD04	<p>CEMS = Continuous emissions monitoring system (CEMS) is not being used.</p> <p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Balancing System = Emissions are not reduced by a vapor balancing system.</p> <p>Documenting Vapor Tightness = Electing to comply with the vapor tightness documentation in 40 CFR 63.567(b)(5)(ii).</p> <p>Vapor Pressure = Vapor pressure is greater than or equal to 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p> <p>Subpart BB Applicability = Marine vessel loading operations are not subject to and complying with 40 CFR Part 61, Subpart BB.</p> <p>Subpart Y Control Device Type = Combustion device other than flare or boiler.</p> <p>Material Loaded = Material other than crude oil or gasoline.</p> <p>HAP Impurities Only = Marine vessel loading operations at loading berths transfer liquids containing organic hazardous air pollutants other than as impurities.</p> <p>Performance Test = Baseline temperature from performance test.</p> <p>Alternate Monitoring = Complying with the control device specific monitoring procedures in 40 CFR § 63.564.</p> <p>Source Emissions = Source with emissions of 10 or 25 tons.</p> <p>Alternate Test Procedure = Electing to comply with the alternate test procedures in 40 CFR § 63.565(m).</p>	None
57-UD1	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
57-UD1	40 CFR Part 61, Subpart J	61J-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS IN BENZENE SERVICE SUBJECT TO NESHAPS J WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
57-UD1	40 CFR Part 61, Subpart V	61V-ALL	SOP Index No. = Owner or operator assumes fugitive unit control requirements for all components in benzene service subject to 40 CFR Part 61, Subpart V with no alternate control or control device.	None
57-UD2	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
57-UDMEC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
57-UDMEC	40 CFR Part 60, Subpart VV	60VV-ALL	SOP Index No. = Owner or operator assumes fugitive unit control requirements for all components in VOC service subject to 40 CFR Part 60, Subpart VV with no alternate control or control devices.	None
57-VC2D7	40 CFR Part 60, Subpart J	60J-FUEL01	<p>Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO<sub>2</sub> emissions into the atmosphere.</p>	None

61-B3E	40 CFR Part 60, Subpart Db	60DB-BOIL01	<p>Alternate Emission Limit (AEL) = The facility combusts byproduct/waste with either natural gas or oil and did not petition the EPA Administrator to establish a NO<sub>x</sub> emission limit that applies specifically when the byproduct/waste is combusted.</p> <p>Construction/Modification Date = On or after November 25, 1986, and on or before July 9, 1997.</p> <p>D-Series Fuel Type #1 = Byproduct/waste.</p> <p>Residual Oil Sampling = The residual oil is not sampled and analyzed for nitrogen content as specified in 40 CFR § 60.49b(e).</p> <p>Heat Input Capacity = Heat input capacity is greater than 100 MMBtu/hr (29 MW) but less than or equal to 250 MMBtu/hr (73 MW).</p> <p>PM Monitoring Type = No particulate monitoring.</p> <p>Facility Type = The affected facility includes a fuel gas combustion device.</p> <p>Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur as defined under 40 CFR § 60.281.</p> <p>Monitoring Device = An instrument is in place for continuous monitoring and recording the concentration (dry basis) of hydrogen sulfide in fuel gasses before being burned in any fuel gas combustion device.</p> <p>NO<sub>x</sub> Monitoring Type = Continuous emission monitoring system.</p> <p>Subpart D = The affected facility does not meet the applicability requirements of 40 CFR Part 60, Subpart D.</p> <p>Common Fuel Source = The fuel gas combustion device has a common fuel source with other fuel gas combustion devices.</p> <p>SO<sub>2</sub> Monitoring Type = No SO<sub>2</sub> monitoring.</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility meets applicability requirements of 40 CFR Part 60, Subpart J.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = None.</p> <p>ACF Option - SO<sub>2</sub> = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = OTHER UNIT TYPE</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>Heat Release Rate = Natural gas oil with a heat release rate greater than 70 MBtu/hr/ft<sup>3</sup>.</p> <p>ACF Option - NO<sub>x</sub> = Other ACF or no ACF.</p>	None
--------	----------------------------	-------------	--	------



Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
61-B3E	40 CFR Part 60, Subpart Db	60DB-BOIL02	<p>Construction/Modification Date = On or after November 25, 1986, and on or before July 9, 1997.</p> <p>D-Series Fuel Type #1 = Natural gas.</p> <p>Residual Oil Sampling = The residual oil is not sampled and analyzed for nitrogen content as specified in 40 CFR § 60.49b(e).</p> <p>Heat Input Capacity = Heat input capacity is greater than 100 MMBtu/hr (29 MW) but less than or equal to 250 MMBtu/hr (73 MW).</p> <p>PM Monitoring Type = No particulate monitoring.</p> <p>Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur as defined under 40 CFR § 60.281.</p> <p>NOx Monitoring Type = Continuous emission monitoring system.</p> <p>Subpart D = The affected facility does not meet the applicability requirements of 40 CFR Part 60, Subpart D.</p> <p>SO2 Monitoring Type = No SO<sub>2</sub> monitoring.</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart J.</p> <p>Subpart E = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart E.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = None.</p> <p>ACF Option - SO2 = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = OTHER UNIT TYPE</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>Heat Release Rate = Natural gas oil with a heat release rate greater than 70 MBtu/hr/ft<sup>3</sup>.</p> <p>ACF Option - NOx = Other ACF or no ACF.</p>	None
61-B3E	40 CFR Part 60, Subpart Dc	60DC-BOIL2	<p>Construction/Modification Date = After June 9, 1989 but on or before February 28, 2005.</p> <p>Maximum Design Heat Input Capacity = Maximum design heat input capacity is greater than 100 MMBtu/hr (29 MW).</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
61-B3E	40 CFR Part 63, Subpart DDDDD	63DDDDD-02	Construction/Reconstruction Date = Construction or reconstruction began on or before June 4, 2010.	None
61-B3E	40 CFR Part 60, Subpart J	60J-FUEL01	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007. Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO <sub>2</sub> emissions into the atmosphere.	None
64-TK0013	30 TAC Chapter 115, Storage of VOCs	115TK-03	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	None
73-FLR442	30 TAC Chapter 111, Visible Emissions	111-FLARE02	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions. Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.	None
73-FLR442	40 CFR Part 60, Subpart A	60A-02	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Steam-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	None
73-FLR442	40 CFR Part 60, Subpart A	60A-03	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Steam-assisted Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec). Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
73-FLR442	40 CFR Part 60, Subpart A	60A-04	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm)</p>	None
73-FLR442	40 CFR Part 63, Subpart A	63A-01	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	None
73-FLR442	40 CFR Part 63, Subpart A	63A-02	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).</p>	None
73-FLR442	40 CFR Part 63, Subpart A	63A-03	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm).</p>	None
73-FLR442	40 CFR Part 60, Subpart J	60J-FUEL01	<p>Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO<sub>2</sub> emissions into the atmosphere.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
73-FLR446	30 TAC Chapter 111, Visible Emissions	111-FLARE02	<p>Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1.</p> <p>Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.</p> <p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p>	None
73-FLR446	40 CFR Part 60, Subpart A	60A-02	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	None
73-FLR446	40 CFR Part 60, Subpart A	60A-03	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).</p>	None
73-FLR446	40 CFR Part 60, Subpart A	60A-04	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm)</p>	None
73-FLR446	40 CFR Part 63, Subpart A	63A-01	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p> <p>Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
73-FLR446	40 CFR Part 63, Subpart A	63A-02	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).</p>	None
73-FLR446	40 CFR Part 63, Subpart A	63A-03	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm).</p>	None
73-FLR446	40 CFR Part 60, Subpart J	60J-FUEL01	<p>Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO<sub>2</sub> emissions into the atmosphere.</p>	None
73-U73F	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
73-U73F	40 CFR Part 63, Subpart CC	63CCVV-1	<p>Any (Instrumentation Systems) = No</p> <p>Closed Vent (Or Vapor Collection) Systems = Yes</p> <p>Enclosed Combustion Device = No</p> <p>Enclosed Combustion Devices = No</p> <p>Existing Source = Yes</p> <p>Flare = Yes</p> <p>Vapor Recovery System = No</p> <p>Any (Closed-Vent Systems) = Yes</p> <p>Closed Vent (Or Vapor Collection) Systems Equivalent Emission Limitation = No</p> <p>Complying with Title 40 CFR 60 Subpart VV = Yes</p> <p>Flare Equivalent Emission Limitation = No</p> <p>AMEL = No</p> <p>Flares = Yes</p> <p>Recovery Or Recapture Devices (Closed Vent Systems) = No</p> <p>Closed Vent (Or Vapor Collection) Systems Complying With § 60.482-10 = Yes</p> <p>Flare Complying With §60.482-10 = Yes</p> <p>Closed Vent System, Bypass Lines = Yes</p> <p>Closed Vent System, Unsafe To Inspect = Yes</p> <p>Closed Vent System, Difficult To Inspect = Yes</p>	None
73-U73F	40 CFR Part 63, Subpart CC	63CCVV-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC/VHAP FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO MACT CC AND COMPLYING WITH NSPS VV REQUIREMENTS WITH NO ALTERNATE CONTROL OR CONTROL DEVICES	None
73-VC447	40 CFR Part 60, Subpart J	60J-FUEL01	<p>Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO<sub>2</sub> emissions into the atmosphere.</p>	None
73-VC448	40 CFR Part 60, Subpart J	60J-FUEL01	<p>Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO<sub>2</sub> emissions into the atmosphere.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
73-VC449	40 CFR Part 60, Subpart J	60J-FUEL01	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007. Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO <sub>2</sub> emissions into the atmosphere.	None
80-DSW	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
80-DSW	40 CFR Part 60, Subpart VV	60VV-ALL	SOP Index No. = Owner or operator assumes fugitive unit control requirements for all components in VOC service subject to 40 CFR Part 60, Subpart VV with no alternate control or control devices.	None
80-DSW	40 CFR Part 61, Subpart J	61J-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS IN BENZENE SERVICE SUBJECT TO NESHAPS J WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
80-DSW	40 CFR Part 61, Subpart V	61V-ALL	SOP Index No. = Owner or operator assumes fugitive unit control requirements for all components in benzene service subject to 40 CFR Part 61, Subpart V with no alternate control or control device.	None
82-CPI	30 TAC Chapter 115, Water Separation	115-CPI01	Alternate Control Requirement = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910. Exemption = Any single or multiple compartment VOC water separator which separates materials having a TVP less than 1.5 psia (10.3 kPa) obtained from any equipment.	None
82-CPI	40 CFR Part 60, Subpart QQQ	60QQQ-CPI1	Construction/Modification Date = AFTER MAY 4, 1987 Control Device = Flare. Alternate Means of Emission Limitation = NO Alternative Monitoring = NO Alternative Standard = NO Capacity < 38 L/s = NO Capacity = DESIGN CAPACITY TO TREAT IS GREATER THAN 16 LITERS/SECOND (250 GAL/MIN) OF REFINERY WASTEWATER.	None
82-FLR454	40 CFR Part 60, Subpart J	60J-FUEL01	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007. Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO <sub>2</sub> emissions into the atmosphere.	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
82-TK0115	30 TAC Chapter 115, Storage of VOCs	115TK-02	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	None
82-TK0116	30 TAC Chapter 115, Storage of VOCs	115TK-07	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
82-TK0117	30 TAC Chapter 115, Storage of VOCs	115TK-07	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
82-TK0605	40 CFR Part 61, Subpart FF	61FF-WWTK1	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Mechanical shoe seal</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	None



Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
82-TK0606	40 CFR Part 61, Subpart FF	61FF-WWTK1	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Mechanical shoe seal</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	None
82-TK0607	40 CFR Part 61, Subpart FF	61FF-WWTK1	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Mechanical shoe seal</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	None
82-TK0608	40 CFR Part 61, Subpart FF	61FF-WWTK1	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Mechanical shoe seal</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	None
83-H1	40 CFR Part 63, Subpart DDDDD	63DDDDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None
83-V105	40 CFR Part 60, Subpart NNN	60NNN-03	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Construction/Modification Date = On or before December 30, 1983.</p>	None
851-TK0925	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
851-TK0925	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
851-TK0925	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
851-TK0926	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
851-TK0926	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
851-TK0926	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
851-TK0927	30 TAC Chapter 115, Storage of VOCs	115TK-06	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	None
851-TK0927	40 CFR Part 60, Subpart Ka	60KA-TK23	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters)</p> <p>True Vapor Pressure = TVP is greater than or equal to 1.5 but less than or equal to 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof (EFR) with mechanical shoe primary seal</p> <p>Reid Vapor Pressure = RVP not determined since 40 CFR § 60.115a(d)(1) exemption is not utilized</p>	None
851-TK0927	40 CFR Part 63, Subpart G	63G-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Two seals, one located above the other, the primary seal being a metallic shoe seal</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p>	None
851-TK0928	30 TAC Chapter 115, Storage of VOCs	115TK-06	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
851-TK0928	40 CFR Part 60, Subpart Ka	60KA-TK23	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters)</p> <p>True Vapor Pressure = TVP is greater than or equal to 1.5 but less than or equal to 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof (EFR) with mechanical shoe primary seal</p> <p>Reid Vapor Pressure = RVP not determined since 40 CFR § 60.115a(d)(1) exemption is not utilized</p>	None
851-TK0928	40 CFR Part 63, Subpart G	63G-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Two seals, one located above the other, the primary seal being a metallic shoe seal</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p>	None
851-TK0929	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
851-TK0929	40 CFR Part 63, Subpart G	63G-03	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>	None
851-TK0930	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
851-TK0930	40 CFR Part 63, Subpart G	63G-03	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>	None
851-TK1029	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
851-TK1029	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
851-TK1029	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
851-TK1030	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
851-TK1030	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
851-TK1030	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
851-TK1031	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
851-TK1031	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
851-TK1031	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
851-TK1032	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
851-TK1032	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
852-TK0201	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
852-TK0201	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK0201	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
852-TK0202	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
852-TK0202	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
852-TK0202	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK0211	30 TAC Chapter 115, Storage of VOCs	115TK-05	Tank Description = Tank using an internal floating roof (IFR) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons	None
852-TK0211	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
852-TK0211	40 CFR Part 63, Subpart CC	63CC-TK11	Existing Source = The storage vessel is at an existing source. Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = Fixed roof and an internal floating roof Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641) Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)	None
852-TK0212	30 TAC Chapter 115, Storage of VOCs	115TK-05	Tank Description = Tank using an internal floating roof (IFR) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons	None
852-TK0212	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None



Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK0212	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
852-TK0221	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
852-TK0221	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
852-TK0221	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
852-TK0222	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK0222	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
852-TK0222	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
852-TK0223	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
852-TK0223	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
852-TK0223	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK0224	30 TAC Chapter 115, Storage of VOCs	115TK-05	Tank Description = Tank using an internal floating roof (IFR) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons	None
852-TK0224	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
852-TK0224	40 CFR Part 63, Subpart G	63G-1	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111) NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = Internal floating roof	None
852-TK0225	30 TAC Chapter 115, Storage of VOCs	115TK-06	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Construction Date = On or after May 12, 1973 Tank Description = Welded tank using an external floating roof Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Primary Seal = Mechanical shoe Storage Capacity = Capacity is greater than 40,000 gallons Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized	None
852-TK0225	40 CFR Part 60, Subpart Ka	60KA-TK23	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters) True Vapor Pressure = TVP is greater than or equal to 1.5 but less than or equal to 11.1 psia Storage Vessel Description = Pontoon-type or double-deck-type external floating roof (EFR) with mechanical shoe primary seal Reid Vapor Pressure = RVP not determined since 40 CFR § 60.115a(d)(1) exemption is not utilized	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK0225	40 CFR Part 63, Subpart G	63G-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Two seals, one located above the other, the primary seal being a metallic shoe seal</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p>	None
852-TK0226	30 TAC Chapter 115, Storage of VOCs	115TK-06	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Construction Date = On or after May 12, 1973</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	None
852-TK0226	40 CFR Part 60, Subpart Ka	60KA-TK23	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters)</p> <p>True Vapor Pressure = TVP is greater than or equal to 1.5 but less than or equal to 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof (EFR) with mechanical shoe primary seal</p> <p>Reid Vapor Pressure = RVP not determined since 40 CFR § 60.115a(d)(1) exemption is not utilized</p>	None
852-TK0226	40 CFR Part 63, Subpart G	63G-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Two seals, one located above the other, the primary seal being a metallic shoe seal</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK0301	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
852-TK0301	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
852-TK0302	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
852-TK0302	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK0302	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
852-TK0401	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
852-TK0401	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
852-TK0401	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK0402	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
852-TK0402	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
852-TK0403	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
852-TK0403	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK0403	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
852-TK0620	40 CFR Part 60, Subpart K	60K-TK02	<p>Construction/Modification Date = After June 11, 1973 And on or before March 8, 1974</p> <p>Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters)</p> <p>Product Stored = Stored product other than petroleum liquid (as defined in 40 CFR Part 60, Subpart K)</p>	None
852-TK0620	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
852-TK0621	40 CFR Part 60, Subpart K	60K-TK02	<p>Construction/Modification Date = After June 11, 1973 And on or before March 8, 1974</p> <p>Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters)</p> <p>Product Stored = Stored product other than petroleum liquid (as defined in 40 CFR Part 60, Subpart K)</p>	None



Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK0621	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
852-TK0804	40 CFR Part 60, Subpart Kb	60KB-TK11	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	None
852-TK0804	40 CFR Part 61, Subpart FF	61FF-WWTK1	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Mechanical shoe seal</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	None
852-TK0804	40 CFR Part 63, Subpart G	63G-WWTK11	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Meets 40 CFR 63.139(d) = The tank does not meet the criteria of 40 CFR § 63.149(d) or the criteria in 40 CFR § 63.149(e)(2).</p> <p>Wastewater Tank Properties = Properties do not qualify for exemption</p> <p>Emission Control Type = Fixed-roof tank equipped with an internal floating roof that meets the requirements specified in 40 CFR § 63.119(b)</p> <p>New Source = The source is an existing source.</p>	<p>-- Affected Pollutant - 112(B) HAPS:</p> <p>Deleted Monitoring/Testing § 63.143(g) was deleted as monitors are not required to be installed for internal floating roof tanks</p> <p>Deleted Reporting § 63.152(c)(3), 63.152(c)(3)(i), and 63.152(c)(3)(ii) as performance tests are not required for internal floating roof tanks</p>

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK1001	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
852-TK1002	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
852-TK1002	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
852-TK1003	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
852-TK1003	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
852-TK1009	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK1009	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
852-TK1010	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
852-TK1015	30 TAC Chapter 115, Storage of VOCs	115TK-07	<p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
852-TK1015	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK1016	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
852-TK1016	40 CFR Part 60, Subpart Kb	60KB-TK12	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	None
852-TK1016	40 CFR Part 63, Subpart CC	63CC-TK02	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 4.0 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK1016	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 4.0 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
852-TK1017	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
852-TK1018	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
852-TK1019	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
852-TK1020	30 TAC Chapter 115, Storage of VOCs	115TK-07	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
852-TK1020	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
852-TK1028	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
852-TK1028	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
853-TK2001	30 TAC Chapter 115, Storage of VOCs	115-TK21	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = Crude oil and/or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
853-TK2001	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
853-TK2002	30 TAC Chapter 115, Storage of VOCs	115TK-04	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
853-TK2002	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
853-TK2002	30 TAC Chapter 115, Storage of VOCs	115TK-21	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = Crude oil and/or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
853-TK2002	40 CFR Part 61, Subpart FF	61FF-WWTK1	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Mechanical shoe seal</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	None
853-TK2002	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
853-TK2002	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
853-TK2003	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None



Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
853-TK2003	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
853-TK2005	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
853-TK2005	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
853-TK2006	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
853-TK2006	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
853-TK3101	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
853-TK3101	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
853-TK3102	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
853-TK3102	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
854-TK0001	30 TAC Chapter 115, Storage of VOCs	115TK-04	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0001	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0001	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0001	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
854-TK0001	40 CFR Part 63, Subpart G	63G-03	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>	None
854-TK0002	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0002	40 CFR Part 60, Subpart K	60K	Construction/Modification Date = On or before June 11, 1973	None
854-TK0002	40 CFR Part 63, Subpart G	63G-TK12	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0003	30 TAC Chapter 115, Storage of VOCs	115TK-04	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0003	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0003	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
854-TK0003	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
854-TK0003	40 CFR Part 63, Subpart G	63G-03	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0004	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0004	40 CFR Part 63, Subpart G	63G-TK11	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	None
854-TK0005	30 TAC Chapter 115, Storage of VOCs	115TK-04	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0005	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0005	30 TAC Chapter 115, Storage of VOCs	115TK-10	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0005	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
854-TK0005	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
854-TK0005	40 CFR Part 63, Subpart G	63G-01	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	None
854-TK0005	40 CFR Part 63, Subpart G	63G-02	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>	None
854-TK0011	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0012	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
854-TK0013	40 CFR Part 63, Subpart G	63G-TK11	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	None
854-TK0014	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
854-TK0014	40 CFR Part 63, Subpart G	63G-01	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	None
854-TK0020	40 CFR Part 63, Subpart G	63G-TK01	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>	None
854-TK0020	40 CFR Part 63, Subpart G	63G-TK11	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0021	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0021	40 CFR Part 61, Subpart FF	61FF-WWTK1	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Mechanical shoe seal</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	None
854-TK0021	40 CFR Part 63, Subpart G	63G-TK12	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	None
854-TK0021	40 CFR Part 63, Subpart G	63G-WWTK11	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Meets 40 CFR 63.139(d) = The tank does not meet the criteria of 40 CFR § 63.149(d) or the criteria in 40 CFR § 63.149(e)(2).</p> <p>Wastewater Tank Properties = Properties do not qualify for exemption</p> <p>Emission Control Type = Fixed-roof tank equipped with an internal floating roof that meets the requirements specified in 40 CFR § 63.119(b)</p> <p>New Source = The source is an existing source.</p>	<p>-- Affected Pollutant - 112(B) HAPS:</p> <p>Deleted Monitoring/Testing § 63.143(g) was deleted as monitors are not required to be installed for internal floating roof tanks</p> <p>Deleted Reporting § 63.152(c)(3), 63.152(c)(3)(i), and 63.152(c)(3)(ii) as performance tests are not required for internal floating roof tanks</p>



Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0022	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0022	40 CFR Part 63, Subpart G	63G-TK12	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	None
854-TK0022	40 CFR Part 63, Subpart G	63G-WWTK11	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Meets 40 CFR 63.139(d) = The tank does not meet the criteria of 40 CFR § 63.149(d) or the criteria in 40 CFR § 63.149(e)(2).</p> <p>Wastewater Tank Properties = Properties do not qualify for exemption</p> <p>Emission Control Type = Fixed-roof tank equipped with an internal floating roof that meets the requirements specified in 40 CFR § 63.119(b)</p> <p>New Source = The source is an existing source.</p>	<p>-- Affected Pollutant - 112(B) HAPS:</p> <p>Deleted Monitoring/Testing § 63.143(g) was deleted as monitors are not required to be installed for internal floating roof tanks</p> <p>Deleted Reporting § 63.152(c)(3), 63.152(c)(3)(i), and 63.152(c)(3)(ii) as performance tests are not required for internal floating roof tanks</p>
854-TK0033	30 TAC Chapter 115, Storage of VOCs	115-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0033	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0033	40 CFR Part 63, Subpart G	63G-TK12	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	None
854-TK0034	30 TAC Chapter 115, Storage of VOCs	115-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0034	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
854-TK0034	40 CFR Part 63, Subpart G	63G-TK12	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	None
854-TK0040	30 TAC Chapter 115, Storage of VOCs	115TK-04	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0040	30 TAC Chapter 115, Storage of VOCs	115TK-05	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.  Tank Description = Tank using an internal floating roof (IFR) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons	None
854-TK0040	40 CFR Part 63, Subpart G	63G-TK01	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.	None
854-TK0041	30 TAC Chapter 115, Storage of VOCs	115TK-04	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.  Tank Description = Tank using an internal floating roof (IFR) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 40,000 gallons	None
854-TK0041	30 TAC Chapter 115, Storage of VOCs	115TK-05	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.  Tank Description = Tank using an internal floating roof (IFR) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons	None
854-TK0041	40 CFR Part 63, Subpart G	63G-TK01	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.	None
854-TK0042	30 TAC Chapter 115, Storage of VOCs	115TK-04	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.  Tank Description = Tank using an internal floating roof (IFR) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 40,000 gallons	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0042	30 TAC Chapter 115, Storage of VOCs	115TK-05	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.  Tank Description = Tank using an internal floating roof (IFR)  Product Stored = VOC other than crude oil or condensate  True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia  Storage Capacity = Capacity is greater than 40,000 gallons	None
854-TK0042	40 CFR Part 63, Subpart G	63G-TK01	MACT Subpart F/G Applicability = The unit is a Group 2 vessel.  NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.  NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.	None
854-TK0043	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
854-TK0043	40 CFR Part 63, Subpart G	63G-03	MACT Subpart F/G Applicability = The unit is a Group 2 vessel.  NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.  NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.	None
854-TK0044	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
854-TK0044	40 CFR Part 63, Subpart G	63G-03	MACT Subpart F/G Applicability = The unit is a Group 2 vessel.  NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.  NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.	None
854-TK0045	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
854-TK0045	40 CFR Part 63, Subpart G	63G-03	MACT Subpart F/G Applicability = The unit is a Group 2 vessel.  NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.  NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.	None
854-TK0050	40 CFR Part 63, Subpart G	63G-TK01	MACT Subpart F/G Applicability = The unit is a Group 2 vessel.  NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.  NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0055	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0055	40 CFR Part 61, Subpart FF	61FF-WWTK2	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the vessel and the edge of the internal floating roof.</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	None
854-TK0055	40 CFR Part 63, Subpart G	63G-WWTK11	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Meets 40 CFR 63.139(d) = The tank does not meet the criteria of 40 CFR § 63.149(d) or the criteria in 40 CFR § 63.149(e)(2).</p> <p>Wastewater Tank Properties = Properties do not qualify for exemption</p> <p>Emission Control Type = Fixed-roof tank equipped with an internal floating roof that meets the requirements specified in 40 CFR § 63.119(b)</p> <p>New Source = The source is an existing source.</p>	<p>-- Affected Pollutant - 112(B) HAPS:</p> <p>Deleted Monitoring/Testing § 63.143(g) was deleted as monitors are not required to be installed for internal floating roof tanks</p> <p>Deleted Reporting § 63.152(c)(3), 63.152(c)(3)(i), and 63.152(c)(3)(ii) as performance tests are not required for internal floating roof tanks</p>
854-TK0056	30 TAC Chapter 115, Storage of VOCs	115TK-04	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0056	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0056	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
854-TK0056	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
854-TK0056	40 CFR Part 63, Subpart G	63G-02	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>	None
854-TK0057	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0057	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
854-TK0060	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
854-TK0061	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
854-TK0062	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0081	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
854-TK0081	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
854-TK0082	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0082	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
854-TK0082	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
854-TK0083	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0083	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None



Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0083	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
854-TK0091	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
854-TK0091	40 CFR Part 60, Subpart Ka	60KA-TK11	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters)</p> <p>True Vapor Pressure = TVP is greater than or equal to 1.5 but less than or equal to 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating-type cover</p> <p>Reid Vapor Pressure = RVP not determined since 40 CFR § 60.115a(d)(1) exemption is not utilized</p>	None
854-TK0092	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
854-TK0092	40 CFR Part 60, Subpart Ka	60KA-TK11	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters) True Vapor Pressure = TVP is greater than or equal to 1.5 but less than or equal to 11.1 psia Storage Vessel Description = Fixed roof with an internal floating-type cover Reid Vapor Pressure = RVP not determined since 40 CFR § 60.115a(d)(1) exemption is not utilized	None
854-TK0093	30 TAC Chapter 115, Storage of VOCs	115TK-05	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons	None
854-TK0093	40 CFR Part 60, Subpart Ka	60KA-TK11	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters) True Vapor Pressure = TVP is greater than or equal to 1.5 but less than or equal to 11.1 psia Storage Vessel Description = Fixed roof with an internal floating-type cover Reid Vapor Pressure = RVP not determined since 40 CFR § 60.115a(d)(1) exemption is not utilized	None
855-TK1018	40 CFR Part 60, Subpart K	60K	Construction/Modification Date = On or before June 11, 1973	None
855-TK1018	40 CFR Part 63, Subpart CC	63CC-TK01	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.	None
855-TK1019	40 CFR Part 60, Subpart K	60K	Construction/Modification Date = On or before June 11, 1973	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
855-TK1019	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
855-TK1022	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
855-TK1022	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
855-TK1022	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
855-TK1022	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
855-TK1023	30 TAC Chapter 115, Storage of VOCs	115TK-04	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
855-TK1023	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
855-TK1023	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
855-TK1023	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
855-TK1024	30 TAC Chapter 115, Storage of VOCs	115TK-05	<p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
855-TK1024	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
855-TK1024	40 CFR Part 63, Subpart CC	63CC-TK11	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	None
855-TK1025	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
855-TK1025	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
855-TK1026	40 CFR Part 60, Subpart K	60K-TK01	Construction/Modification Date = On or before June 11, 1973	None
855-TK1026	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
855-TK1027	30 TAC Chapter 115, Storage of VOCs	115TK-22	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	None
855-TK1027	40 CFR Part 60, Subpart Ka	60KA-TK22	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters)</p> <p>True Vapor Pressure = TVP is greater than or equal to 1.5 but less than or equal to 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof (EFR) with mechanical shoe primary seal</p> <p>Reid Vapor Pressure = RVP not determined since 40 CFR § 60.115a(d)(1) exemption is not utilized</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
855-TK1027	40 CFR Part 63, Subpart G	63G-TK22	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Two seals, one located above the other, the primary seal being a metallic shoe seal</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p>	None
855-TK1040	40 CFR Part 63, Subpart G	63G-03	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>	None
855-TK1041	30 TAC Chapter 115, Storage of VOCs	115TK-07	<p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	None
855-TK1041	40 CFR Part 60, Subpart Ka	60KA-TK22	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters)</p> <p>True Vapor Pressure = TVP is less than 1.5 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof (EFR) with mechanical shoe primary seal</p> <p>Reid Vapor Pressure = Reid vapor pressure is less than 1.0 psia</p> <p>Maximum True Vapor Pressure = Maximum true vapor pressure is less than or equal to 1.0 psia</p>	None
855-TK1041	40 CFR Part 63, Subpart G	63G-03	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
855-TK1042	30 TAC Chapter 115, Storage of VOCs	115TK-06	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.  Tank Description = Welded tank using an external floating roof  Product Stored = VOC other than crude oil or condensate  True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia  Primary Seal = Mechanical shoe  Storage Capacity = Capacity is greater than 40,000 gallons  Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized	None
855-TK1042	30 TAC Chapter 115, Storage of VOCs	115TK-07	Tank Description = Tank does not require emission controls  Product Stored = VOC other than crude oil or condensate  True Vapor Pressure = True vapor pressure is less than 1.0 psia  Storage Capacity = Capacity is greater than 40,000 gallons	None
855-TK1042	40 CFR Part 60, Subpart Ka	60KA-TK23	Product Stored = Petroleum liquid (other than petroleum or condensate)  Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters)  True Vapor Pressure = TVP is greater than or equal to 1.5 but less than or equal to 11.1 psia  Storage Vessel Description = Pontoon-type or double-deck-type external floating roof (EFR) with mechanical shoe primary seal  Reid Vapor Pressure = RVP not determined since 40 CFR § 60.115a(d)(1) exemption is not utilized	None
855-TK1042	40 CFR Part 63, Subpart G	63G-1	MACT Subpart F/G Applicability = The unit is a Group 2 vessel.  NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.  NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.	None
89-U89	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
90-UD3	30 TAC Chapter 115, Loading and Unloading of VOC	115-LOAD22	Chapter 115 Facility Type = Marine terminal	None
911-H	40 CFR Part 63, Subpart DDDD	63DDDD-01	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	None



Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
911-H	40 CFR Part 60, Subpart Dc	60DC-BOIL3	Construction/Modification Date = On or before June 9, 1989.	None
911-H	40 CFR Part 60, Subpart J	60J-FUEL01	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b). Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.  Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO <sub>2</sub> emissions into the atmosphere.	None
97-D3FUG	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
DEAUNLOAD	40 CFR Part 63, Subpart EEEE	63EEEE	Existing Source = Source is an existing source Transfer Operation = Transfer rack only unloads organic liquids Transfer Volume = Less than 800,000 gallons of organic containing liquids are transferred by the organic loading distribution facility annually. Weight Percent HAP = Liquids transferred contain 98 percent by weight or greater HAP	None
DIESELLOAD	30 TAC Chapter 115, Loading and Unloading of VOC	115-LOAD02	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline. Transfer Type = Only loading. True Vapor Pressure = True vapor pressure is less than 1.5 psia.	-- Affected Pollutant - VOC:  Deleted Related Standard § 115.214(b)(1)(D) and 115.214(b)(1)(D)(i) as these exemptions for fumes from hatches or vents do not apply to this loading operation
ENGVENT01	30 TAC Chapter 111, Visible Emissions	111-ENGVENT01	Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113. Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit. Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3). Construction Date = After January 31, 1972 Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
F066	30 TAC Chapter 111, Visible Emissions	111-VENT03	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = A continuous emissions monitoring system (CEMS) capable of measuring the opacity of emissions is installed in the vent in accordance with 30 TAC § 111.111(a)(1)(C).</p> <p>Total Feed Capacity = Total feed capacity is less than or equal to 20,000 barrels per day.</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	None
F416	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
F416	40 CFR Part 60, Subpart GGG	60GGG-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS IN VOC SERVICE SUBJECT TO NSPS GGG WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
FUG-FGRS	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
FUG-FGRS	40 CFR Part 63, Subpart CC	63CCVV-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC/VHAP FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO MACT CC AND COMPLYING WITH NSPS VV REQUIREMENTS WITH NO ALTERNATE CONTROL OR CONTROL DEVICES	None
FUG-GHT	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
FUG-GHT	40 CFR Part 60, Subpart GGG	60GGG-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS IN VOC SERVICE SUBJECT TO NSPS GGG WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
FUG-GHT	40 CFR Part 60, Subpart GGGa	60GGGa-1	<p>Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006.</p> <p>Equipment Components = Components are present.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
FUG-GHT	40 CFR Part 63, Subpart CC	63CCVV-2	Compressor In Hydrogen Service = Yes Existing Source = Yes Open-Ended Valves Or Lines = No Pressure Relief Device In Gas/Vapor Service = No Pressure Relief Device In Heavy Liquid Service = No Vacuum Service = Yes Valves In Heavy Liquid Service = Yes Complying With Title 40 CFR 60 Subpart VV = Yes Pump In Light Liquid Service = Yes Valves In Heavy Liquid Service Equivalent Emission Limitation = No AMEL = No Compressor Equivalent Emission Limitation = No Pump Equivalent Emission Limitation = No Valves In Heavy Liquid Service Complying With § 60.482-8 = Yes Compressor Complying With § 60.482-3 = Yes Flanges And Other Connectors = Yes Pump Complying With § 60.482-2 = Yes Sampling Connection Systems = Yes Valves In Gas/Vapor Or Light Liquid Service = Yes Flanges And Other Connectors Equivalent Emission Limitation = No Pump In Heavy Liquid Service = Yes Sampling Connection System Equivalent Emission Limitation = No Valves In Gas/Vapor Or Light Liquid Service Equivalent Emission Limitation = No Pump Equivalent Emission Limitation = No Flanges And Other Connectors Complying With § 60.482-8 = Yes Sampling Connection Systems Complying With § 60.482-5 = Yes Valves In Gas/Vapor Or Light Liquid Service Complying With § 60.482-7 = Yes Pump Complying With § 60.482-8 = Yes	None
GASUNLOAD	30 TAC Chapter 115, Loading and Unloading of VOC	115-LOAD01	Chapter 115 Facility Type = Motor vehicle fuel dispensing facility	None
GRP1CT	40 CFR Part 63, Subpart Q	63Q-CT01	Used Compounds Containing Chromium on or After September 8, 1994 = The industrial process cooling tower has not used compounds containing chromium on or after September 8, 1994.	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP1DOCK	30 TAC Chapter 115, Loading and Unloading of VOC	115-LOAD22	Chapter 115 Facility Type = Marine terminal	None
GRP1DOCK	40 CFR Part 61, Subpart BB	61BB-LOAD2	Negative Applicability = The loading rack loads only benzene-laden waste, gasoline, crude oil, natural gas liquids, petroleum distillates or benzene-laden liquid from a coke by-product plant.	None
GRP1DOCK	40 CFR Part 63, Subpart CC	63CC-LOAD2	Specified in 63.640(g)(1)-(6) = The gasoline loading rack or marine vessel loading operation is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63, Subparts F, G, H or I = The gasoline loading rack or marine vessel loading operation is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Unit Type = Marine vessel loading operation at a petroleum refinery meeting the applicability criteria of 40 CFR § 63.560.	None
GRP1DOCK	40 CFR Part 63, Subpart Y	63Y-LOAD01	Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore). Ballasting Operations = Ballasting operations are the only operations performed at the facility.	None
GRP1DOCK	40 CFR Part 63, Subpart Y	63Y-LOAD02	Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore). Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility. Vapor Pressure = Vapor pressure is less than 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP1DOCK	40 CFR Part 63, Subpart Y	63Y-LOAD03	<p>CEMS = Continuous emissions monitoring system (CEMS) is not being used.</p> <p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Balancing System = Emissions are not reduced by a vapor balancing system.</p> <p>Documenting Vapor Tightness = Electing to comply with the vapor tightness documentation in 40 CFR 63.567(b)(5)(ii).</p> <p>Vapor Pressure = Vapor pressure is greater than or equal to 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p> <p>Subpart BB Applicability = Marine vessel loading operations are not subject to and complying with 40 CFR Part 61, Subpart BB.</p> <p>Subpart Y Control Device Type = Combustion device other than flare or boiler.</p> <p>Material Loaded = Gasoline.</p> <p>HAP Impurities Only = Marine vessel loading operations at loading berths transfer liquids containing organic hazardous air pollutants other than as impurities.</p> <p>Performance Test = Baseline temperature from performance test.</p> <p>Alternate Monitoring = Complying with the control device specific monitoring procedures in 40 CFR § 63.564.</p> <p>Source Emissions = Source with emissions of 10 or 25 tons.</p> <p>Alternate Test Procedure = Electing to comply with the alternate test procedures in 40 CFR § 63.565(m).</p> <p>Throughput = Source with throughput of 10 M barrels or 200 M barrels.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP1DOCK	40 CFR Part 63, Subpart Y	63Y-LOAD04	<p>CEMS = Continuous emissions monitoring system (CEMS) is not being used.</p> <p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Balancing System = Emissions are not reduced by a vapor balancing system.</p> <p>Documenting Vapor Tightness = Electing to comply with the vapor tightness documentation in 40 CFR 63.567(b)(5)(ii).</p> <p>Vapor Pressure = Vapor pressure is greater than or equal to 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p> <p>Subpart BB Applicability = Marine vessel loading operations are not subject to and complying with 40 CFR Part 61, Subpart BB.</p> <p>Subpart Y Control Device Type = Combustion device other than flare or boiler.</p> <p>Material Loaded = Material other than crude oil or gasoline.</p> <p>HAP Impurities Only = Marine vessel loading operations at loading berths transfer liquids containing organic hazardous air pollutants other than as impurities.</p> <p>Performance Test = Baseline temperature from performance test.</p> <p>Alternate Monitoring = Complying with the control device specific monitoring procedures in 40 CFR § 63.564.</p> <p>Source Emissions = Source with emissions of 10 or 25 tons.</p> <p>Alternate Test Procedure = Electing to comply with the alternate test procedures in 40 CFR § 63.565(m).</p>	None
GRP1HTR	40 CFR Part 60, Subpart J	60J-FUEL01	<p>Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO<sub>2</sub> emissions into the atmosphere.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP1PRO	40 CFR Part 63, Subpart F	63F-PRO01	<p>Applicable Chemicals = The chemical manufacturing process unit manufactures, as a primary product, one or more of the chemicals listed in 40 CFR § 63.100(b)(1)(i) or 40 CFR § 63.100(b)(1)(ii).</p> <p>Intervening Cooling Fluid = There is no intervening cooling fluid containing less than 5 percent by weight of total HAPs listed in Table 4 of 40 CFR Part 63, Subpart F, between the process and cooling water.</p> <p>Table 2 HAP = The chemical manufacturing process unit uses as a reactant or manufactures, as a product or co-product, one or more of the organic hazardous air pollutants in Table 2.</p> <p>Table 4 HAP Content = The recirculating heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 4 of title 40 CFR Part 63, Subpart F.</p> <p>Alternate Means of Emission Limitation = No alternative means of emission limitation has been approved by the EPA Administrator to achieve a reduction in organic HAP emission or no alternate has been requested.</p> <p>NPDES Permit = The once-through heat exchange system is not subject to NPDES permit with an allowable discharge limit of 1 part per million or less above influent concentration or 10 percent or less above influent concentration.</p> <p>Meets 40 CFR 63.104(a)(4)(i)-(iv) = The once-through heat exchange system is not subject to an NPDES permit that meets 40 CFR § 63.104(a)(4)(i) - (iv).</p> <p>Heat Exchange System = A heat exchange system is utilized.</p> <p>Table 9 HAP Content = The once-through heat exchange system is used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 9 of 40 CFR Part 63, Subpart G.</p> <p>Cooling Water Monitored = The cooling water is being monitored for the presence of one or more HAPs or other representative substances whose presence in cooling water indicates a leak.</p> <p>Cooling Water Pressure = The heat exchange system is not operated with the minimum pressure on the cooling water side at least 35 kilopascals greater than the maximum pressure on the process side.</p>	None
GRP1STACK	30 TAC Chapter 111, Visible Emissions	111-VENT01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP2DOCK	30 TAC Chapter 115, Loading and Unloading of VOC	115-LOAD22	Chapter 115 Facility Type = Marine terminal	None
GRP2DOCK	40 CFR Part 61, Subpart BB	61BB-LOAD2	Negative Applicability = The loading rack loads only benzene-laden waste, gasoline, crude oil, natural gas liquids, petroleum distillates or benzene-laden liquid from a coke by-product plant.	None
GRP2DOCK	40 CFR Part 63, Subpart CC	63CC-LOAD1	Specified in 63.640(g)(1)-(6) = The gasoline loading rack or marine vessel loading operation is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).  Subject to 40 CFR Part 63, Subparts F, G, H or I = The gasoline loading rack or marine vessel loading operation is not subject to 40 CFR Part 63, Subparts F, G, H, or I.  Unit Type = Gasoline loading rack not classified under Standard Industrial Classification code 2911 or marine vessel loading operation at a petroleum refinery not meeting the applicability criteria of 40 CFR § 63.560.	None
GRP2DOCK	40 CFR Part 63, Subpart Y	63Y-LOAD02	Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).  Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.  Vapor Pressure = Vapor pressure is less than 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.	None
GRP2FUG	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None



Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP2FUG	40 CFR Part 63, Subpart CC	63CCVV-ALL	<p>Closed Vent (Or Vapor Collection) Systems = Yes</p> <p>Enclosed Combustion Device = No</p> <p>Existing Source = Yes</p> <p>Flare = Yes</p> <p>Vapor Recovery System = Yes</p> <p>Closed Vent (Or Vapor Collection) Systems Equivalent Emission Limitation = No</p> <p>Complying With Title 40 CFR 60 Subpart VV = Yes</p> <p>Flare Equivalent Emission Limitation = No</p> <p>Vapor Recovery System Equivalent Emission Limitation = No</p> <p>AMEL = No</p> <p>Closed Vent (Or Vapor Collection) Systems Complying With § 60.482-10 = Yes</p> <p>Flare Complying With §60.482-10 = Yes</p> <p>Vapor Recovery System Complying With § 60.482-10 = Yes</p>	None
GRP2STACK	30 TAC Chapter 111, Visible Emissions	111-VENT01	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	None
GRP3FUG	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP3FUG	40 CFR Part 63, Subpart H	63H-ALL	<p>Sop Index No. = Owner/Operator Assumes Fugitive Control Requirements For All Components In VOC Or VHAP Service Subject To 40 CFR Part 63, Subpart H With No Alternated Control Or Control Device.</p> <p>Any (Closed Vent Systems) = Component Present</p> <p>Bypass Lines = Fugitive Unit Contains Any Closed-Vent Systems Containing By-Pass Lines That Could Divert A Vent Stream Away From The Control Device And To The Atmosphere</p> <p>Equipment Type = Fugitive Unit Contains Equipment Listed In 40 CFR § 63.160(A) Which Is Operated In Organic Hazardous Air Pollutant Service</p> <p>Non Research And Development/Batch Processes = Fugitive Unit Contains Processes Other Than Research And Development Facilities And Bench-Scale Batch Processes</p> <p>Recovery Or Recapture Devices (Closed Vent Systems) = Component Not Present</p> <p>Unsafe To Inspect = Fugitive Unit Contains Any Closed-Vent System With Parts Designated As Unsafe To Inspect</p> <p>Difficult To Inspect = Fugitive Unit Contains Any Closed-Vent System With Parts Designated As Difficult To Inspect</p> <p>Vacuum Service = Not All Of The Equipment In The Fugitive Unit Is In Vacuum Service</p> <p>Enclosed Combustion Devices (Closed Vent Systems) = Component Not Present</p> <p>Less Than 300 Operating Hours = The Fugitive Unit Does Not Contain Any Equipment In Organic Hazardous Air Pollutant (Hap) Service That Is Intended To Operate Less Than 300 Hours Per Calendar Year</p> <p>Heavy Liquid Service = None Of The Equipment In Organic Hap Service That Is Intended To Operate Less Than 300 Hours Per Calendar Year Is In Heavy Liquid Service</p> <p>AMEL = Fugitive Unit Source Owner/Operator Is Not Electing To Comply With An Alternative Means Of Emission Limitation (AMEL)</p> <p>Flares (Closed Vent Systems) = Component Present</p>	None
GRP4FUG	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
GRP-CCVT3	40 CFR Part 60, Subpart NNN	60NNN-02	Subpart NNN Chemicals = The distillation unit does not produce any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.	None
GRPDEGRSR	30 TAC Chapter 115, Degreasing Processes	115-SOLV11	<p>Solvent Degreasing Machine Type = Degreasing operations located on a property which, when uncontrolled, can emit a combined weight of VOC less than 550 pounds in any consecutive 24-hour period.</p> <p>Alternate Control Requirement = The TCEQ Executive Director has not approved an alternative control requirement as allowed under 30 TAC § 115.413 or not alternative has been requested.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP-HONVT	40 CFR Part 63, Subpart G	63G-VENT01	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p>	None
GRP-NNNVT1	40 CFR Part 60, Subpart NNN	60NNN-01	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 not from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved through use of a flare or recovery device.</p> <p>Subpart NNN Control Device = Flare.</p> <p>Vent Type = Distillation unit not discharging vent stream into a vapor recovery system.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	None
GRP-R5VT2	40 CFR Part 60, Subpart NNN	60NNN-03	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Construction/Modification Date = On or before December 30, 1983.</p>	None
GRP-R5VT3	40 CFR Part 60, Subpart NNN	60NNN-02	<p>Subpart NNN Chemicals = The distillation unit does not produce any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p>	None
GRPVENDTKS	30 TAC Chapter 115, Storage of VOCs	115TK-01	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPVENDTKS	30 TAC Chapter 115, Storage of VOCs	115TK-02	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.  Tank Description = Tank does not require emission controls  Product Stored = VOC other than crude oil or condensate  True Vapor Pressure = True vapor pressure is less than 1.0 psia  Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	None
GRPVENDTKS	30 TAC Chapter 115, Storage of VOCs	115TK-03	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.  Tank Description = Tank using a submerged fill pipe  Product Stored = VOC other than crude oil or condensate  True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia  Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	None
GRPVENDTKS	30 TAC Chapter 115, Storage of VOCs	115TK-31	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.  Product Stored = Other than crude oil, condensate, or VOC	None
GRPVENDTKS	40 CFR Part 60, Subpart Kb	60Kb-1	Product Stored = Petroleum liquid (other than petroleum or condensate)  Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	None
GRPVENDTKS	40 CFR Part 60, Subpart Kb	60Kb-10	Product Stored = Waste mixture of indeterminate or variable composition  Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	None
GRPVENDTKS	40 CFR Part 60, Subpart Kb	60Kb-11	Product Stored = Waste mixture of indeterminate or variable composition  Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)  Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia	None
GRPVENDTKS	40 CFR Part 60, Subpart Kb	60Kb-12	Product Stored = Waste mixture of indeterminate or variable composition  Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)  Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia	None
GRPVENDTKS	40 CFR Part 60, Subpart Kb	60Kb-13	Product Stored = Stored product other than volatile organic liquid or petroleum liquid	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPVENDTKS	40 CFR Part 60, Subpart Kb	60Kb-2	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	None
GRPVENDTKS	40 CFR Part 60, Subpart Kb	60Kb-3	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia	None
GRPVENDTKS	40 CFR Part 60, Subpart Kb	60Kb-4	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia	None
GRPVENDTKS	40 CFR Part 60, Subpart Kb	60Kb-5	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	None
GRPVENDTKS	40 CFR Part 60, Subpart Kb	60Kb-6	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	None
GRPVENDTKS	40 CFR Part 60, Subpart Kb	60Kb-7	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia	None
GRPVENDTKS	40 CFR Part 60, Subpart Kb	60Kb-8	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia	None
GRPVENDTKS	40 CFR Part 60, Subpart Kb	60Kb-9	Product Stored = Waste mixture of indeterminate or variable composition Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPVENDTKS	40 CFR Part 63, Subpart CC	63CC-TK01	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	None
GRPVENDTKS	40 CFR Part 63, Subpart CC	63CC-TK03	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p>	None
PCEUNLOAD	40 CFR Part 63, Subpart EEEE	63EEEE	<p>Existing Source = Source is an existing source</p> <p>Transfer Operation = Transfer rack only unloads organic liquids</p> <p>Transfer Volume = Ten million gallons or more of organic containing liquids are transferred by the organic loading distribution facility annually.</p> <p>Weight Percent HAP = Liquids transferred contain 25 percent by weight or greater HAP</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
PROBTXTRTR	40 CFR Part 61, Subpart FF	61FF-TRT01	<p>AMOC = An alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.348 for treatment processes is not used.</p> <p>By-Pass Line = The closed-vent system does not contain a by-pass line that could divert the vent stream away from the control device.</p> <p>Continuous Monitoring = The wastewater treatment system unit process parameters are continuously monitored to indicate proper system operation.</p> <p>Complying with § 61.342(e) = The facility is complying with 40 CFR § 61.342(e).</p> <p>Control Device Type/Operation = Thermal vapor incinerator that provides a minimum residence time of 0.5 seconds at a minimum temperature of 760 degrees C.</p> <p>Openings = The treatment process or wastewater treatment system unit has no openings.</p> <p>Fuel Gas System = Not all gaseous vent streams from the treatment process or wastewater treatment system are routed to a fuel gas system.</p> <p>Benzene Removal = Benzene is removed from the waste stream to a level of less than 10 ppmw on a flow weighted annual average basis.</p> <p>Engineering Calculations = Performance tests are used show that the control device achieves its emission limitation.</p> <p>Closed-Vent System and Control Device = A closed-vent system and control device is used.</p> <p>Process Or Stream Exemption = The treatment process or waste stream is not complying with 40 CFR §61.348(d).</p> <p>AMOC = No alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.349 for a closed-vent system and control device is used.</p> <p>Treatment Process Engineering Calculations = Performance tests are used to show that the treatment process or wastewater treatment system unit achieves its emission limitation.</p>	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
PROBTXTRTR	40 CFR Part 63, Subpart G	63G-TRT01	<p>Combustion Process = No combustion process is used for treatment.</p> <p>Compliance With 40 CFR § 63.139(c)(1) = The enclosed combustion device being used meets the 0.5 second residence time at 760 degrees C provisions specified in 40 CFR § 63.139(c)(1)(iii).</p> <p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Fuel Gas System = The closed anaerobic biological treatment process is not vented through hard-piping to a fuel gas system.</p> <p>Series Design Evaluation = Compliance for the series of treatment processes is demonstrated using performance testing.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.148.</p> <p>Performance Tests = Design evaluation is used to demonstrate that the control device or combination of control devices achieves the appropriate conditions.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Designated as Group 1 per 40 CFR § 63.132(e).</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Percent mass removal/destruction option by reducing the mass flow rate by the 99 percent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of § 63.143(e)(1) or § 63.143(e)(2) in Table 13 of Subpart G.</p> <p>Control Devices = Thermal vapor incinerator.</p> <p>Treatment Process Design Evaluation = Compliance for the treatment process will be demonstrated by performance test.</p>	<p>-- Affected Pollutant - 112(B) HAPS:</p> <p>Added Monitoring/Testing § 63.148(g)(1) as an exemption for inspection of any part of the closed vent system that is determined to be unsafe to inspect</p> <p>Added Monitoring/Testing § 63.148(h)(1) was added as an exemption for inspection of any part of the closed vent system that is determined to be difficult to inspect</p> <p>Added Reporting § 63.146(b)(7), 63.146(b)(7)(ii), 63.146(b)(7)(ii)(A), 63.146(b)(7)(ii)(B) which are applicable reporting requirements for non-flare control devices</p>



Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
PRODFDTRTR	40 CFR Part 61, Subpart FF	61FF-TRT02	<p>AMOC = An alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.348 for treatment processes is not used.</p> <p>Continuous Monitoring = The wastewater treatment system unit process parameters are continuously monitored to indicate proper system operation.</p> <p>Complying with § 61.342(e) = The facility is complying with 40 CFR § 61.342(e).</p> <p>Openings = The treatment process or wastewater treatment system unit has no openings.</p> <p>Fuel Gas System = Not all gaseous vent streams from the treatment process or wastewater treatment system are routed to a fuel gas system.</p> <p>Benzene Removal = Benzene is removed from the waste stream to a level of less than 10 ppmw on a flow weighted annual average basis.</p> <p>Closed-Vent System and Control Device = A closed-vent system and control device is not used.</p> <p>Process Or Stream Exemption = The treatment process or waste stream is not complying with 40 CFR §61.348(d).</p> <p>Treatment Process Engineering Calculations = Performance tests are used to show that the treatment process or wastewater treatment system unit achieves its emission limitation.</p>	None
PROEPSRU	30 TAC Chapter 112, Sulfur Compounds	112-SRU01	<p>Sulfur Recovery Plant = The gas sweetening unit is using sulfur recovery.</p> <p>Stack Height = Effective stack height greater than or equal to the standard effective stack height.</p>	None
PROEPSRU	40 CFR Part 60, Subpart J	60J-SRU1	<p>Facility Type = Claus sulfur recovery plant with a design capacity for sulfur feed greater than 20 LTPD with oxidation control systems.</p> <p>Construction/Modification Date = After October 4, 1976 and on or before May 14, 2007.</p>	None
PROEPSRU	40 CFR Part 63, Subpart UUU	63UUU-3	<p>SRU Emission Limitation = Claus SRU part of sulfur recovery plant greater than or equal to 20 long tons/day using oxidation or reduction system followed by incineration subject to 250 ppmv SO<sub>2</sub> emission limit in §60.104(a)(2).</p> <p>SRU Monitoring Method = CEMS for monitoring reduced sulfur and O<sub>2</sub> concentrations.</p> <p>SRU Bypass Line = No bypass line serving the SRU.</p>	None
SCOTFUG	30 TAC Chapter 115, Fugitives Pet Ref B Counties	R5322-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO CHAPTER 115 SUBCHAPTER D DIVISION 2 WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None
SCOTFUG	40 CFR Part 60, Subpart GGG	60GGG-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS IN VOC SERVICE SUBJECT TO NSPS GGG WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	None

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
SLDGLOAD	30 TAC Chapter 115, Loading and Unloading of VOC	115-LOAD02	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.  Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.  Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.  Transfer Type = Only loading.  True Vapor Pressure = True vapor pressure is less than 1.5 psia.	-- Affected Pollutant - VOC:  Deleted Related Standard § 115.214(b)(1)(D) and 115.214(b)(1)(D)(i) as these exemptions for fumes from hatches or vents do not apply to this loading operation
SLDGLOAD	40 CFR Part 61, Subpart BB	61BB-LOAD1	Negative Applicability = The loading rack loads only benzene-laden waste, gasoline, crude oil, natural gas liquids, petroleum distillates or benzene-laden liquid from a coke by-product plant.	
SURFCOAT	30 TAC Chapter 115, Surface Coating Operations	115-COAT01	Alternative Compliance Method = No alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria has been approved by the TCEQ Executive Director or no such alternate has been requested.  Facility Operations = Surface coating operation meeting §115.427(7)	

\* - The "unit attributes" or operating conditions that determine what requirements apply

\*\* - Notes changes made to the automated results from the DSS, and a brief explanation why

## NSR Versus Title V FOP

The state of Texas has two Air permitting programs, New Source Review (NSR) and Title V Federal Operating Permits. The two programs are substantially different both in intent and permit content.

NSR is a preconstruction permitting program authorized by the Texas Clean Air Act and Title I of the Federal Clean Air Act (FCAA). The processing of these permits is governed by 30 Texas Administrative Code (TAC) Chapter 116.111. The Title V Federal Operating Program is a federal program authorized under Title V of the FCAA that has been delegated to the state of Texas to administer and is governed by 30 TAC Chapter 122. The major differences between the two permitting programs are listed in the table below:

NSR Permit	Federal Operating Permit(FOP)
Issued Prior to new Construction or modification of an existing facility	For initial permit with application shield, can be issued after operation commences; significant revisions require approval prior to operation.
Authorizes air emissions	Codifies existing applicable requirements, does not authorize new emissions
Ensures issued permits are protective of the environment and human health by conducting a health effects review and that requirement for best available control technology (BACT) is implemented.	Applicable requirements listed in permit are used by the inspectors to ensure proper operation of the site as authorized. Ensures that adequate monitoring is in place to allow compliance determination with the FOP.
Up to two Public notices may be required. Opportunity for public comment and contested case hearings for some authorizations.	One public notice required. Opportunity for public comments. No contested case hearings.
Applies to all point source emissions in the state.	Applies to all major sources and some non-major sources identified by the EPA.
Applies to facilities: a portion of site or individual emission sources	One or multiple FOPs cover the entire site (consists of multiple facilities)
Permits include terms and conditions under which the applicant must construct and operate its various equipment and processes on a facility basis.	Permits include terms and conditions that specify the general operational requirements of the site; and also include codification of all applicable requirements for emission units at the site.
Opportunity for EPA review for Federal Prevention of Significant Deterioration (PSD) and Nonattainment (NA) permits for major sources.	Opportunity for EPA review, Affected states review, and a Public petition period for every FOP.
Permits have a table listing maximum emission limits for pollutants	Permit has an applicable requirements table and Periodic Monitoring (PM) / Compliance Assurance Monitoring (CAM) tables which document applicable monitoring requirements.
Permits can be altered or amended upon application by company. Permits must be issued before construction or modification of facilities can begin.	Permits can be revised through several revision processes, which provide for different levels of public notice and opportunity to comment. Changes that would be significant revisions require that a revised permit be issued before those changes can be operated.
NSR permits are issued independent of FOP requirements.	FOP are independent of NSR permits, but contain a list of all NSR permits incorporated by reference

## New Source Review Requirements

Below is a list of the New Source Review (NSR) permits for the permitted area. These NSR permits are incorporated by reference into the operating permit and are enforceable under it. These permits can be found in the main TCEQ file room, located on the first floor of Building E, 12100 Park 35 Circle, Austin, Texas. In addition, many of the permits are accessible online through the link provided below. The Public Education Program may be contacted at 1-800-687-4040 or the Air Permits Division (APD) may be contacted at 1-512-239-1250 for help with any question.

Additionally, the site contains emission units that are permitted by rule under the requirements of 30 TAC Chapter 106, Permits by Rule. Permit by Rule (PBR) registrations submitted by permittees are also available online through the link provided below. The following table specifies the PBRs that apply to the site.

The TCEQ has interpreted the emission limits prescribed in 30 TAC §106.4(a) as both emission thresholds and default emission limits. The emission limits in 30 TAC §106.4(a) are all considered applicable to each facility as a threshold matter to ensure that the owner/operator qualifies for the PBR authorization. Those same emission limits are also the default emission limits if the specific PBR does not further limit emissions or there is no lower, certified emission limit claimed by the owner/operator.

This interpretation is consistent with how TCEQ has historically determined compliance with the emission limits prior to the addition of the “as applicable” language. The “as applicable” language was added in 2014 as part of changes to the sentence structure in a rulemaking that made other changes to address greenhouse gases and was not intended as a substantive rule change. This interpretation also provides for effective and practical enforcement of 30 TAC §106.4(a), since for the TCEQ to effectively enforce the emission limits in 30 TAC §106.4(a) as emission thresholds, all emission limits must apply. As provided by 30 TAC §106.4(a)(2) and (3), an owner/operator shall not claim a PBR authorization if the facility is subject to major New Source Review. The practical and legal effect of the language in 30 TAC § 106.4 is that if a facility does not emit a pollutant, then the potential to emit for that particular pollutant is zero, and thus, the facility is not authorized to emit the pollutant pursuant to the PBR.

The status of air permits, applications, and PBR registrations may be found by performing the appropriate search of the databases located at the following website:

[www.tceq.texas.gov/permitting/air/nav/air\\_status\\_permits.html](http://www.tceq.texas.gov/permitting/air/nav/air_status_permits.html)

Details on how to search the databases are available in the **Obtaining Permit Documents** section below.

### New Source Review Authorization References

Prevention of Significant Deterioration (PSD) Permits	
PSD Permit No.: PSDTX36	Issuance Date: 06/22/2018
PSD Permit No.: PSDTX653M1	Issuance Date: 06/22/2018
PSD Permit No.: PSDTX831	Issuance Date: 12/06/2013
PSD Permit No.: PSDTX96	Issuance Date: 06/27/2018
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 141429	Issuance Date: 11/14/2017
Authorization No.: 149242	Issuance Date: 12/12/2018
Authorization No.: 17677A	Issuance Date: 12/10/2012
Authorization No.: 19044	Issuance Date: 05/31/2018
Authorization No.: 20156	Issuance Date: 04/18/2017
Authorization No.: 21303	Issuance Date: 11/26/2013

### New Source Review Authorization References

Authorization No.: 21358	Issuance Date: 06/06/2018
Authorization No.: 21706	Issuance Date: 03/31/2016
Authorization No.: 22312	Issuance Date: 12/06/2013
Authorization No.: 2695A	Issuance Date: 06/22/2018
Authorization No.: 2697A	Issuance Date: 06/22/2018
Authorization No.: 2699A	Issuance Date: 03/31/2016
Authorization No.: 2700A	Issuance Date: 06/11/2015
Authorization No.: 2703A	Issuance Date: 06/22/2018
Authorization No.: 2704A	Issuance Date: 07/08/2016
Authorization No.: 2705A	Issuance Date: 03/31/2016
Authorization No.: 2706A	Issuance Date: 03/31/2016
Authorization No.: 2708A	Issuance Date: 06/22/2018
Authorization No.: 3119A	Issuance Date: 06/05/2018
Authorization No.: 3123A	Issuance Date: 06/27/2018
Authorization No.: 3857A	Issuance Date: 10/28/2005
Authorization No.: 46637	Issuance Date: 10/05/2017
Authorization No.: 46640	Issuance Date: 07/07/2017
Authorization No.: 46641	Issuance Date: 06/27/2018
Authorization No.: 46642	Issuance Date: 02/13/2012
Authorization No.: 5418A	Issuance Date: 06/22/2018
Authorization No.: 6722A	Issuance Date: 06/27/2018
Authorization No.: 72654	Issuance Date: 06/28/2018
Authorization No.: 80521	Issuance Date: 08/04/2016
Authorization No.: 80801	Issuance Date: 06/22/2018
Authorization No.: 8653A	Issuance Date: 03/08/2011
Authorization No.: 9604A	Issuance Date: 06/22/2018
<b>Permits By Rule (30 TAC Chapter 106) for the Application Area</b>	
Number: 106.183	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 12/24/1998
Number: 106.261	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 12/24/1998
Number: 106.262	Version No./Date: 09/04/2000
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001

### New Source Review Authorization References

Number: 106.371	Version No./Date: 09/04/2000
Number: 106.433	Version No./Date: 09/04/2000
Number: 106.454	Version No./Date: 11/01/2001
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 03/14/1997
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.492	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000
Number: 106.512	Version No./Date: 06/13/2001
Number: 106.532	Version No./Date: 09/04/2000
Number: 14	Version No./Date: 06/07/1996
Number: 15	Version No./Date: 09/23/1982
Number: 51	Version No./Date: 09/12/1989
Number: 53	Version No./Date: 09/12/1989
Number: 57	Version No./Date: 04/04/1975
Number: 58	Version No./Date: 05/12/1981
Number: 61	Version No./Date: 09/12/1989
Number: 61	Version No./Date: 10/04/1995
Number: 62	Version No./Date: 05/12/1981
Number: 63	Version No./Date: 05/12/1981
Number: 80	Version No./Date: 05/04/1994
Number: 80	Version No./Date: 06/07/1996
Number: 86	Version No./Date: 08/30/1988
Number: 86	Version No./Date: 09/12/1989
Number: 86	Version No./Date: 09/13/1993
Number: 86	Version No./Date: 05/04/1994
Number: 88	Version No./Date: 07/20/1992
Number: 102	Version No./Date: 01/08/1980
Number: 106	Version No./Date: 08/30/1988
Number: 106	Version No./Date: 07/20/1992
Number: 106	Version No./Date: 04/05/1995
Number: 111	Version No./Date: 09/12/1989
Number: 111	Version No./Date: 07/20/1992
Number: 118	Version No./Date: 01/08/1980

## New Source Review Authorization References

Number: 118	Version No./Date: 04/05/1995
-------------	------------------------------

### Emission Units and Emission Points

In air permitting terminology, any source capable of generating emissions (for example, an engine or a sandblasting area) is called an Emission Unit. For purposes of Title V, emission units are specifically listed in the operating permit when they have applicable requirements other than New Source Review (NSR), or when they are listed in the permit shield table.

The actual physical location where the emissions enter the atmosphere (for example, an engine stack or a sand-blasting yard) is called an emission point. For New Source Review preconstruction permitting purposes, every emission unit has an associated emission point. Emission limits are listed in an NSR permit, associated with an emission point. This list of emission points and emission limits per pollutant is commonly referred to as the "Maximum Allowable Emission Rate Table", or "MAERT" for short. Specifically, the MAERT lists the Emission Point Number (EPN) that identifies the emission point, followed immediately by the Source Name, identifying the emission unit that is the source of those emissions on this table.

Thus, by reference, an emission unit in a Title V operating permit is linked by reference number to an NSR authorization, and its related emission point.

### Monitoring Sufficiency

Federal and state rules, 40 CFR § 70.6(a)(3)(i)(B) and 30 TAC § 122.142(c) respectively, require that each federal operating permit include additional monitoring for applicable requirements that lack periodic or instrumental monitoring (which may include recordkeeping that serves as monitoring) that yields reliable data from a relevant time period that are representative of the emission unit's compliance with the applicable emission limitation or standard. Furthermore, the federal operating permit must include compliance assurance monitoring (CAM) requirements for emission sources that meet the applicability criteria of 40 CFR Part 64 in accordance with 40 CFR § 70.6(a)(3)(i)(A) and 30 TAC § 122.604(b).

With the exception of any emission units listed in the Periodic Monitoring or CAM Summaries in the FOP, the TCEQ Executive Director has determined that the permit contains sufficient monitoring, testing, recordkeeping, and reporting requirements that assure compliance with the applicable requirements. If applicable, each emission unit that requires additional monitoring in the form of periodic monitoring or CAM is described in further detail under the Rationale for CAM/PM Methods Selected section following this paragraph.

## Rationale for Periodic Monitoring Methods Selected

### Periodic Monitoring:

The Federal Clean Air Act requires that each federal operating permit include monitoring sufficient to assure compliance with the terms and conditions of the permit. Most of the emission limits and standards applicable to emission units at Title V sources include adequate monitoring to show that the units meet the limits and standards. For those requirements that do not include monitoring, or where the monitoring is not sufficient to assure compliance, the federal operating permit must include such monitoring for the emission units affected. The following emission units are subject to periodic monitoring requirements because the emission units are subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement that does not already require monitoring, or the monitoring for the applicable requirement is not sufficient to assure compliance:

Unit/Group/Process Information	
ID No.: 47-TK0103	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115-1
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Structural integrity of the pipe is in question and not repaired before refilling.	
<b>Basis of monitoring:</b> The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.	



Unit/Group/Process Information	
ID No.: 47-TK0103	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115-1
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Discharge opening not entirely submerged when pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: 54-TK3	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 64-TK0013	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-03
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Discharge opening not entirely submerged when pipe used to withdraw liquid from the tank; tank can no longer withdraw liquid in normal operation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: 64-TK0013	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-03
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Structural integrity of the pipe is in question and is not repaired before refilling.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: 851-TK0925	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 851-TK0926	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 851-TK1029	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 851-TK1030	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	



Unit/Group/Process Information	
ID No.: 851-TK1031	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 852-TK0201	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 852-TK0202	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 852-TK0211	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 852-TK0212	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 852-TK0221	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 852-TK0222	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 852-TK0223	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	



Unit/Group/Process Information	
ID No.: 852-TK0224	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 852-TK0301	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 852-TK0302	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 852-TK0401	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 852-TK0402	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 852-TK0403	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 852-TK1009	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 852-TK1016	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	



Unit/Group/Process Information	
ID No.: 853-TK2001	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115-TK21
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 853-TK2002	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 853-TK2002	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-21
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0001	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0002	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0003	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0004	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0005	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	



Unit/Group/Process Information	
ID No.: 854-TK0021	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0022	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0033	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115-1
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0034	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115-1
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0040	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0041	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0042	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0055	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	



Unit/Group/Process Information	
ID No.: 854-TK0056	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0057	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0082	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0083	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0091	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0091	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Ka	SOP Index No.: 60KA-TK11
Pollutant: VOC	Main Standard: § 60.112a(a)(2)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0092	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0092	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Ka	SOP Index No.: 60KA-TK11
Pollutant: VOC	Main Standard: § 60.112a(a)(2)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	



Unit/Group/Process Information	
ID No.: 854-TK0093	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 854-TK0093	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Ka	SOP Index No.: 60KA-TK11
Pollutant: VOC	Main Standard: § 60.112a(a)(2)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 855-TK1022	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 855-TK1023	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: 855-TK1024	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-05
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: ENGVENT01	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: 111-ENGVENT01
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: Presence of visible emissions is a deviation, or 20% or greater opacity is a deviation	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: GRP1STACK	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: 111-VENT01
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: Presence of visible emissions is a deviation, or 15% or greater opacity is a deviation	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: GRP2STACK	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: 111-VENT01
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: Presence of visible emissions is a deviation, or 15% or greater opacity is a deviation	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	



Unit/Group/Process Information	
ID No.: GRPVENDTKS	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-03
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Structural integrity of the pipe is in question and not repaired before refilling.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: GRPVENDTKS	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: 115TK-03
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Discharge opening not entirely submerged when pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: PROEPSRU	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: 112-SRU01
Pollutant: SO <sub>2</sub>	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: SO <sub>2</sub> Concentration	
Minimum Frequency: four times per hour	
Averaging Period: hourly	
Deviation Limit: Greater than 250 ppm hourly average or greater than 250 ppm on a 12-hour rolling average.	
Basis of monitoring: It is widely practiced and accepted to calibrate and use a portable analyzer or CEMS to measure SO <sub>2</sub> concentration with procedures such as EPA Test Method 6C. The measured concentration along with stack flow rate or AP-42 factors and fuel consumption records may be used to demonstrate compliance with an underlying emission limit or standard.	

## Obtaining Permit Documents

The New Source Review Authorization References table in the FOP specifies all NSR authorizations that apply at the permit area covered by the FOP. Individual NSR permitting files are located in the TCEQ Central File Room (TCEQ Main Campus located at 12100 Park 35 Circle, Austin, Texas, 78753, Building E, Room 103). They can also be obtained electronically from TCEQ's Central File Room Online (<https://www.tceq.texas.gov/goto/cfr-online>). Guidance documents that describe how to search electronic records, including Permits by Rule (PBRs) or NSR permits incorporated by reference into an FOP, archived in the Central File Room server are available at [https://www.tceq.texas.gov/permitting/air/nav/air\\_status\\_permits.html](https://www.tceq.texas.gov/permitting/air/nav/air_status_permits.html)

All current PBRs are contained in Chapter 106 and can be viewed at the following website:

[https://www.tceq.texas.gov/permitting/air/permitbyrule/air\\_pbr\\_index.html](https://www.tceq.texas.gov/permitting/air/permitbyrule/air_pbr_index.html)

Previous versions of 30 TAC Chapter 106 PBRs may be viewed at the following website:

[www.tceq.texas.gov/permitting/air/permitbyrule/historical\\_rules/old106list/index106.html](http://www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/old106list/index106.html)

Historical Standard Exemption lists may be viewed at the following website:

[www.tceq.texas.gov/permitting/air/permitbyrule/historical\\_rules/oldselist/se\\_index.html](http://www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/oldselist/se_index.html)

Additional information concerning PBRs is available on the TCEQ website:

[https://www.tceq.texas.gov/permitting/air/nav/air\\_pbr.html](https://www.tceq.texas.gov/permitting/air/nav/air_pbr.html)

## Available Unit Attribute Forms

- OP-UA1 - Miscellaneous and Generic Unit Attributes
- OP-UA2 - Stationary Reciprocating Internal Combustion Engine Attributes
- OP-UA3 - Storage Tank/Vessel Attributes
- OP-UA4 - Loading/Unloading Operations Attributes
- OP-UA5 - Process Heater/Furnace Attributes
- OP-UA6 - Boiler/Steam Generator/Steam Generating Unit Attributes
- OP-UA7 - Flare Attributes
- OP-UA8 - Coal Preparation Plant Attributes
- OP-UA9 - Nonmetallic Mineral Process Plant Attributes
- OP-UA10 - Gas Sweetening/Sulfur Recovery Unit Attributes
- OP-UA11 - Stationary Turbine Attributes
- OP-UA12 - Fugitive Emission Unit Attributes
- OP-UA13 - Industrial Process Cooling Tower Attributes
- OP-UA14 - Water Separator Attributes
- OP-UA15 - Emission Point/Stationary Vent/Distillation Operation/Process Vent Attributes
- OP-UA16 - Solvent Degreasing Machine Attributes
- OP-UA17 - Distillation Unit Attributes
- OP-UA18 - Surface Coating Operations Attributes
- OP-UA19 - Wastewater Unit Attributes
- OP-UA20 - Asphalt Operations Attributes
- OP-UA21 - Grain Elevator Attributes
- OP-UA22 - Printing Attributes
- OP-UA24 - Wool Fiberglass Insulation Manufacturing Plant Attributes
- OP-UA25 - Synthetic Fiber Production Attributes
- OP-UA26 - Electroplating and Anodizing Unit Attributes
- OP-UA27 - Nitric Acid Manufacturing Attributes
- OP-UA28 - Polymer Manufacturing Attributes
- OP-UA29 - Glass Manufacturing Unit Attributes
- OP-UA30 - Kraft, Soda, Sulfite, and Stand-Alone Semichemical Pulp Mill Attributes

OP-UA31 - Lead Smelting Attributes  
OP-UA32 - Copper and Zinc Smelting/Brass and Bronze Production Attributes  
OP-UA33 - Metallic Mineral Processing Plant Attributes  
OP-UA34 - Pharmaceutical Manufacturing  
OP-UA35 - Incinerator Attributes  
OP-UA36 - Steel Plant Unit Attributes  
OP-UA37 - Basic Oxygen Process Furnace Unit Attributes  
OP-UA38 - Lead-Acid Battery Manufacturing Plant Attributes  
OP-UA39 - Sterilization Source Attributes  
OP-UA40 - Ferroalloy Production Facility Attributes  
OP-UA41 - Dry Cleaning Facility Attributes  
OP-UA42 - Phosphate Fertilizer Manufacturing Attributes  
OP-UA43 - Sulfuric Acid Production Attributes  
OP-UA44 - Municipal Solid Waste Landfill/Waste Disposal Site Attributes  
OP-UA45 - Surface Impoundment Attributes  
OP-UA46 - Epoxy Resins and Non-Nylon Polyamides Production Attributes  
OP-UA47 - Ship Building and Ship Repair Unit Attributes  
OP-UA48 - Air Oxidation Unit Process Attributes  
OP-UA49 - Vacuum-Producing System Attributes  
OP-UA50 - Fluid Catalytic Cracking Unit Catalyst Regenerator/Fuel Gas Combustion Device/Claus Sulfur Recovery Plant Attributes  
OP-UA51 - Dryer/Kiln/Oven Attributes  
OP-UA52 - Closed Vent Systems and Control Devices  
OP-UA53 - Beryllium Processing Attributes  
OP-UA54 - Mercury Chlor-Alkali Cell Attributes  
OP-UA55 - Transfer System Attributes  
OP-UA56 - Vinyl Chloride Process Attributes  
OP-UA57 - Cleaning/Depainting Operation Attributes  
OP-UA58 - Treatment Process Attributes  
OP-UA59 - Coke By-Product Recovery Plant Attributes  
OP-UA60 - Chemical Manufacturing Process Unit Attributes  
OP-UA61 - Pulp, Paper, or Paperboard Producing Process Attributes  
OP-UA62 - Glycol Dehydration Unit Attributes  
OP-UA63 - Vegetable Oil Production Attributes